



# GREEN POWER GP 6000XM/LM SINGLE- PHASE DIESEL GENERATOR STAGEV 5,6KVA

Product price:

**1,664.00 € tax excluded**

## Product description:

### **GREEN POWER GP 6000XM/LM SINGLE-PHASE DIESEL GENERATOR STAGEV 5,6KVA**

The generator GREENPOWER GP 6000XM/LM single-phase is equipped with a KOHLER 15440 **StageV** engine supplied by Diesel, and is complete with capacitor voltage regulator (**AVR optional**).

GREENPOWER GP 6000XM/LM is equipped with manual recoil start with self winding and has a low fuel consumption, in fact it consumes only 1,6 liter/hour at 75% of load for a range of up to 3,1 hours of operation.

The GREENPOWER GP 6000XM/LM generator provides reliable power for home, work and recreation environments Safely appliances and other electronic devices Power solution for outdoor parties. Extremely convenient plugs and controls make starting and operating the generator easy and quick.

The GREENPOWER GP 6000XM/LM generator has a convenient double-curved handle for easy mobility and storage. GREENPOWER GP 6000XM/LM has a completely steel structure and a tank with a maximum capacity of 5 liters. The generator guarantees an efficient and silent operation thanks to the KOHLER 15440 StageV engine that allows to deliver a maximum power of 5,6KVA.

## **STAGEV EMISSION STANDARD**

The acronym STAGEV defines the guidelines and limits of gas emissions from engines. The



regulation is respected through the installation of special anti-particulate filters in the gensets, but an indispensable condition for the filter to work correctly is that the genset works at its design temperature.

#### TECHNICAL CHARACTERISTICS GREENPOWER GP 6000XM/LM

Phase Type: Single Phase  
Continuous Use Power: 5 KVA / 5 KW  
Maximum Power: 5.6 KVA / 5.6 KW  
Motor: KOHLER 15440  
Engine RPM: 3000 rpm  
Emission Standard: StageV  
Starting: Manual recoil  
Fuel: Diesel  
Voltage: 230 V  
Frequency: 50 Hz  
Socket panel: 1 x Schuko 16A 230V / 1 x 16A 230V CEE  
Fuel tank capacity: 5 l  
Autonomy at 75% load: 3.1 h  
Consumption at 75% load: 1,6Lt/h  
Length: 780 mm  
Width: 570 mm  
Height: 680 mm  
Dry weight: 85 Kg

Are you looking for a generator with different technical characteristics? [Here](#) you can find the area dedicated to GREENPOWER generators or other specialized brands.

Images and technical data not binding.

#### Product features:

Phase: Single phase  
Maximum power single phase (KW): 5.6  
Continuous power single phase (KW): 5  
Maximum power single phase (KVA): 5.6  
Continuous power single phase (KVA): 5  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230  
Sockets configuration: 1 x Schuko 16A 230V / 1 x 16A 230V CEE  
Engine: Kohler KD 15-440  
Emissions Regulations: Stage 5



Engine rpm (rpm): 3000  
Starting system: Pull starter with recoil  
Engine capacity (cm<sup>3</sup>): 436  
Number cylinders: 1  
Cooling: Air  
Alternator: LINZ SP10 MG  
Poles: 2  
Fuel tank capacity (L): 5  
Consumption (L/h): 1.6 al 75% del carico  
Running time (h): 3.1 al 75% del carico  
Length (mm): 780  
Width (mm): 570  
Height (mm): 680  
Dry weight (Kg): 85  
Silenced: No  
Super silenced: No  
ATS Switch device : No  
Voltage regulator: Capacitor / AVR (optional)  
Engine manufacturer: Kohler