



GREEN POWER GP 4000XM/YE SINGLE-PHASE GENERATOR ELECTRIC START DIESEL STAGEV 3,5KVA

Product price:

1,885.00 € tax excluded

Product description:

GREENPOWER GP 4000XM/YE SINGLE-PHASE GENERATOR ELECTRIC START DIESEL STAGEV 3,5KVA

The generator GREENPOWER GP 4000XM/YE single-phase, is equipped with a YANMAR L70AE **StageV** Diesel-supplied engine, complete with capacitor voltage regulator (**AVR optional**).

GREENPOWER GP 4000XM/YE is equipped with electric start and has a low fuel consumption, in fact it consumes only 1,2 liter/hour at 75% of load for a range of up to 3 hours of operation.

The generator provides reliable power for home, work and recreational environments, safely appliances and other electronic devices. Extremely convenient sockets and controls make starting and operating the generator easy and fast.

The GREENPOWER GP 4000XM/YE generator has a convenient double-curved handle for easy mobility and storage, has a completely steel structure and a tank with a maximum capacity of 3,5 liters. The generator guarantees an efficient and silent operation thanks to the YANMAR L70AE StageV engine with electric start, which can deliver a maximum power of 3.5KVA.

STAGEV EMISSION STANDARDS

The acronym STAGEV defines the guidelines and limits of gas emissions from engines. The regulation is respected through the installation of special anti-particulate filters in the gensets, but an indispensable condition for the filter to work correctly is that the genset works at its design temperature.



TECHNICAL FEATURES GREENPOWER GP 4000XM/YE

Phase Type: Single-phase

Continuous Duty: 3.1 KVA / 3.1 KW Maximum Power: 3.5 KVA / 3.5 KW

Engine: YANMAR L70AE Engine RPM: 3000 rpm

Emission Regulation: Stage V

Starting: Electric Fuel: Diesel Voltage: 230 V Frequency: 50 Hz

Socket panel: 2 x Schuko 16A 230V

Tank capacity: 3,5 I

Autonomy at 75% load: 3 h

Consumption at 75% load: 1,2 Lt/h

Length: 780 mm Width: 570 mm Height: 680 mm Dry weight: 80 Kg

Are you looking for a generator with different technical characteristics? <u>HERE</u> you can find the area dedicated to GREENPOWER generators or other specialized brands.

Images and technical data are not binding.

Product features:

Phase: Single phase

Maximum power single phase (KW): 3.5 Continuous power single phase (KW): 3.1 Maximum power single phase (KVA): 3.5 Continuous power single phase (KVA): 3.1

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 230

Sockets configuration: 2 x 230V 16A SCHUKO

Engine: Yanmar L70AE, 4 stroke Emissions Regulations: Stage 5

Engine rpm (rpm): 3000 Starting system: Elettrico Engine capacity (cm³): 296

Number cylinders: 1



Cooling: Air

Alternator: LINZ SP10 SE

Poles: 2

Fuel tank capacity (L): 3.5

Consumption (L/h):

Running time (h): 3 al 75% del carico

Length (mm): 780 Width (mm): 570 Height (mm): 680 Dry weight (Kg): 80

Silenced: No

Super silenced: No

ATS Switch device : Optional

Voltage regulator: Capacitor / AVR (optional)

Engine manufacturer: Yanmar

