



GREEN POWER GP 17000XM/LE SINGLE-PHASE DIESEL GENERATOR ELECTRIC START 16,3KVA

Product price:

4.664,00 € tax excluded

Product description:

GREEN POWER GP 17000XM/LE SINGLE-PHASE DIESEL GENERATOR ELECTRIC START 16,3KVA

The generator GREEN POWER GP 17000XM/LE single-phase, is equipped with a KOHLER KD 625-2 engine powered by Diesel, and is complete with capacitor voltage regulator (AVR optional).

GREEN POWER GP 17000XM/LE features a large 10-liter fuel tank and low fuel consumption, only 4 liters/hour at 75% load for up to 2.5 hours of operation. Extremely practical sockets and controls make starting and operating the generator easy and quick.

The alternator of the generator is the LINZ E1C13MD model (or equivalent primary brand) and is synchronous, single phase, with brushes and with class H insulation, in addition it is equipped with a voltage regulator. The generator is ducted with a practical electric start system, so you can start the unit without any effort.

The generator is compact and convenient to maneuver and carry thanks to its compact size, as well as practical tubular handles. In addition, it is equipped with a practical and convenient electric start system, so that it can be put into operation quickly and easily.

The GREEN POWER GP 17000XM/LE generator is equipped with a high-performance KOHLER KD 625-2 engine that allows this machine to deliver a maximum single-phase power of 16.3KVA.

The electric control panel of the GREEN POWER GP 17000XM/LE is composed of:





- Sockets: 1 x 63A 3P 230V / 1 x 16A 3P 230V
- Voltmeter
- Starting key
- Hour meter
- Ammeter
- Frequency meter
- Low oil pressure Led
- Mains presence Led
- Circuit breaker + differential

TECHNICAL FEATURES GREEN POWER GP 17000XM/LE

Phase Type: Single Phase

Continuous Use output: 15 KVA / 15 KW Maximum output: 16.3 KVA / 16.3 KW

Motor: KOHLER KD 625-2 Motor RPM: 3000 rpm

Emissions Standard: Non-Emitting

Firing: Electric Fuel: Diesel Voltage: 230 V Frequency: 50 Hz

Socket panel: 1 x 63A 3P 230V / 1 x 16A 3P 230V

Tank capacity: 10 I

Run time at 75% load: 2. 5 h Consumption at 75% load: 4 Lt/h

Length: 1200 mm Width: 620 mm Height: 970 mm Dry weight: 253 Kg

Are you looking for a generator with different technical features? HERE you can find the area dedicated to GREEN POWER generators or other specialized brands.

Images and technical data are not binding.

Product features:

Phase: Single phase

Maximum power single phase (KW): 16.3 Continuous power single phase (KW): 15 Maximum power single phase (KVA): 16.3 Continuous power single phase (KVA): 15





Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 230

Sockets configuration: 1 x 63A 3P 230V / 1 x 16A 3P 230V

Engine: Kohler KD 625/2

Emissions Regulations: Stationary Use

Engine rpm (rpm): 3000 Starting system: Elettrico Engine capacity (cm³): 1248

Number cylinders: 2

Cooling: Air

Alternator: LINZ E1C13MD

Poles: 2

Fuel tank capacity (L): 10

Consumption (L/h): 4 al 75% del carico Running time (h): 2.5 at 75% of the load

Length (mm): 1200 Width (mm): 620 Height (mm): 970 Dry weight (Kg): 253

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device: Optional

Voltage regulator: Capacitor / AVR (optional)

Engine manufacturer: Kohler

