



GREEN POWER GP 17000 SM/LDE SILENT GENERATOR SINGLE- PHASE ELECTRICAL START 16,3KVA

Product price:

5,836.00 € tax excluded

Product description:

GREEN POWER GP 17000 SM/LDE SILENT GENERATOR SINGLE-PHASE ELECTRICAL START 16,3KVA

The generator GREEN POWER GP 17000 SM/LDE single-phase, is equipped with a KOHLER KD625-2 Diesel-supplied engine, complete with capacitor voltage regulator (**AVR optional**).

GREEN POWER GP 17000 SM/LDE is equipped with electric start and has a low fuel consumption, in fact it consumes only 4 liters/hour at 75% of the load for an autonomy of up to 12,5 hours of operation.

The generator GREEN POWER GP 17000 SM/LDE is equipped with silenced casing that can be opened in two sections made of sheet 20/10, soundproofing material in class 1, internal muffler. Thanks to these devices, the generator can be considered super-silenced, with a noise emission of only 77 dB recorded at a distance of 7 meters from the source.

The generator guarantees efficient and silent operation thanks to the KOHLER KD625-2 engine, which allows to deliver a maximum power of 16,3KVA.

ATS AUTOMATIC STARTING FRAME

The GREEN POWER GP 17000 SM/LDE generator is designed for use with an ATS automatic start-up panel. Thanks to this, you will no longer have to worry about blackouts, in the event of a power failure this panel is able to automatically turn on the generator and allow you to continue your business.



The generator control panel consists of:

- Thermomagnetic circuit breaker and isolation control
- Sockets: 1 x 16A 3P 230V / 1 x 63A 3P 230V
- ATS arrangement
- Voltmeter
- Ammeter
- Hour meter
- Ignition switch
- Emergency stop button

TECHNICAL FEATURES GREEN POWER GP 17000 SM/LDE

Phase Type: Single-phase

Continuous output: 14,8 KVA / 14,8 KW

Maximum output: 16,3 KVA / 16,3 KW

Motor: KOHLER KD625-2

Engine speed: 3000 rpm

Emission regulation: NOT Emitted

Starting: Electric

Fuel: Diesel

Voltage: 230 V

Frequency: 50 Hz

Socket panel: 1 x 16A 3P 230V / 1 x 63A 3P 230V

Tank capacity: 50 l

Runtime at 75% load: 12. 5 h

Consumption at 75% load: 4 Lt/h

Acoustic pressure: 77 dB(A) @ 7 m

Length: 1200 mm

Width: 700 mm

Height: 1050 mm

Dry weight: 390 Kg

Are you looking for a generator with different technical characteristics? [Here](#) you can find the area dedicated to GREENPOWER generators or other specialized brands.

Images and technical data not binding.

Product features:



Phase: Single phase

Maximum power single phase (KW): 16.3

Continuous power single phase (KW): 14.8

Maximum power single phase (KVA): 16.3

Continuous power single phase (KVA): 14.8

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230

Sockets configuration: 1 x 16A 3P 230V / 1 x 63A 3P 230V

Engine: Kohler KD 625/2

Emissions Regulations: Stationary Use

Engine rpm (rpm): 3000

Starting system: Elettrico

Engine capacity (cm³): 1248

Number cylinders: 2

Cooling: Air

Alternator: LINZ E1C13MD/2

Poles: 2

Fuel tank capacity (L): 50

Consumption (L/h): 4 al 75% del carico

Running time (h): 12,5 at 75% load

Acoustic pressure: 77 dB(A) at 7 m

Length (mm): 1200

Width (mm): 700

Height (mm): 840

Dry weight (Kg):

Silenced: Yes

Super silenced: Yes

ATS Switch device : Optional

Voltage regulator: Capacitor / AVR (optional)

Engine manufacturer: Kohler

