



BADA 10SE ELECTIRC LIFTER AISI 304 STAINLESS STEEL 1000Kg CAPACITY

Product price:

12,013.00 € tax excluded

Product description:

BADA 10SE ELECTIRC LIFTER AISI 304 STAINLESS STEEL 1000Kg CAPACITY

BADA 10SE is a lifter in stainless steel AISI 304 with electric lifting up to 2900 mm, designed to position goods at the ideal height and reduce the operator's effort during the operations of picking up and putting down the goods.

BADA 10SE thanks to its constructive characteristics, and to the construction entirely in **stainless steel AISI 304** can be used in the agri-food, chemical and pharmaceutical industry.

Resistant, easy to handle and with an ergonomic design, it fully meets the most stringent hygienic requirements as it can be sanitized by regular high-pressure washing. BADA 10SE is of side handles to direct the trolley and braking system on a directing wheel.

BADA 10SE is a manual lifter entirely made of AISI 304 stainless steel (including the lifting pump and hydraulic components), suitable for use in wet and corrosive environments where impeccable cleanliness and hygiene are required and corrosion problems caused by the use of acids and salt solutions must be solved. The bearings are waterproof and the rollers are made of nylon with a polyurethane cover making them extremely resistant and further minimizing maintenance costs.

The BADA 10SE lifter **ON EXPLICIT REQUEST OF THE CUSTOMER** can be supplied in AISI 316 stainless steel (**Optional WITH surcharge**).

TECHNICAL FEATURES BADA 10SE

Traction: Manual

Load center of gravity: 600 mm

Wheelbase: 1230 mm



Own weight including battery: 380 kg
Tire: polyurethane
Front wheels size: 175 x 40 mm
Rear wheels dimensions: 82 x 90 mm
Number of front / rear wheels: 2 / 2
Front track width: 683 mm
Rear track width: 380 mm
Lowered mast height: 2.078 / 1.978 mm
Fork lift stroke: 1.560 / 2.810 mm
Mast height extended: 2,078 / 3,340 mm
Height of drawbar in driving position min / max: 724 / 1.223 mm
Lowered fork height: 90 mm
Total length: 1,740 mm
Length including fork heel: 590 mm
Total width: 779 mm
Fork thickness: 55 mm
Fork width: 180 mm
Fork length: 1,150 mm
Working aisle width: 1,860 mm
Bending radius: 1.313 mm
Lifting speed with / without load: 0.05 - 0.04 m/s
Lowering speed with / without load 0.19 - 0.13 m/s
Manual operating brake
Construction material: Stainless steel AISI 304
Lifting motor: 1.8 KW
Voltage, nominal battery capacity 12 / 140 V/Ah

Are you looking for a pallet truck with different technical characteristics? [HERE](#) you can find the area dedicated to BADA or other Transpallet specialized brands.

Images and technical data are not binding.

Product features:

Drive: Manual
Operator type:
Load capacity (Kg): 1000
Service weight (Kg): 320 / 380
Tyres: front wheels: POLY.I. / NYLON
Tyres: rear wheels:
Quantity rear wheels: 2
Quantity front wheels: 2
Rear balancing axle: No



Lift height (mm): 1650 / 2900

Height of tiller in drive position max (mm): 1223

Height of tiller in drive position min (mm): 724

Height lowered (mm):

Overall length (mm): 1740

Overall width (mm): 780

Width fork (mm): 180

Length fork (mm):

Distance between fork arms (mm): 200

Turning radius (mm): 1313

Weigher: No

Type of lifting: Electric