



# BADA 10SE ELECTIRC LIFTER AISI 304 STAINLESS STEEL 1000Kg CAPACITY

Product price:

**12.013,00 € tax excluded**

## Product description:

BADA 10SE ELECTIRC LIFTER AISI 304 STAINLESS STEEL 1000Kg CAPACITY

BADA 10SE is a lifter in stainless steel AISI 304 with electric lifting up to 2900 mm, designed to position goods at the ideal height and reduce the operator's effort during the operations of picking up and putting down the goods.

BADA 10SE thanks to its constructive characteristics, and to the construction entirely in **stainless steel AISI 304** can be used in the agri-food, chemical and pharmaceutical industry.

Resistant, easy to handle and with an ergonomic design, it fully meets the most stringent hygienic requirements as it can be sanitized by regular high-pressure washing. BADA 10SE is of side handles to direct the trolley and braking system on a directing wheel.

BADA 10SE is a manual lifter entirely made of AISI 304 stainless steel (including the lifting pump and hydraulic components), suitable for use in wet and corrosive environments where impeccable cleanliness and hygiene are required and corrosion problems caused by the use of acids and salt solutions must be solved. The bearings are waterproof and the rollers are made of nylon with a polyurethane cover making them extremely resistant and further minimizing maintenance costs.

The BADA 10SE lifter **ON EXPLICIT REQUEST OF THE CUSTOMER** can be supplied in AISI 316 stainless steel ( **Optional WITH surcharge** ).

## TECHNICAL FEATURES BADA 10SE

Traction: Manual

Load center of gravity: 600 mm

Wheelbase: 1230 mm





Own weight including battery: 380 kg  
Tire: polyurethane  
Front wheels size: 175 x 40 mm  
Rear wheels dimensions: 82 x 90 mm  
Number of front / rear wheels: 2 / 2  
Front track width: 683 mm  
Rear track width: 380 mm  
Lowered mast height: 2.078 / 1.978 mm  
Fork lift stroke: 1.560 / 2.810 mm  
Mast height extended: 2,078 / 3,340 mm  
Height of drawbar in driving position min / max: 724 / 1.223 mm  
Lowered fork height: 90 mm  
Total length: 1,740 mm  
Length including fork heel: 590 mm  
Total width: 779 mm  
Fork thickness: 55 mm  
Fork width: 180 mm  
Fork length: 1,150 mm  
Working aisle width: 1,860 mm  
Bending radius: 1.313 mm  
Lifting speed with / without load: 0.05 - 0.04 m/s  
Lowering speed with / without load 0.19 - 0.13 m/s  
Manual operating brake  
Construction material: Stainless steel AISI 304  
Lifting motor: 1.8 KW  
Voltage, nominal battery capacity 12 / 140 V/Ah

Are you looking for a pallet truck with different technical characteristics? [HERE](#) you can find the area dedicated to BADA or other Transpallet specialized brands.

Images and technical data are not binding.

#### **Product features:**

Drive: Manual  
Operator type:  
Load capacity (Kg): 1000  
Service weight (Kg): 320 / 380  
Tyres: front wheels: POLY.I. / NYLON  
Tyres: rear wheels:  
Quantity rear wheels: 2  
Quantity front wheels: 2  
Rear balancing axle: No





Lift height (mm): 1650 / 2900  
Height of tiller in drive position max (mm): 1223  
Height of tiller in drive position min (mm): 724  
Height lowered (mm): 90  
Overall length (mm): 1740  
Overall width (mm): 780  
Width fork (mm): 180  
Length fork (mm):  
Distance between fork arms (mm): 200  
Turning radius (mm): 1313  
Weigher: No  
Type of lifting: Electric