



GENERATOR SUPERSILENCED 9,5KVA 50/60 Hz SINGLE-PHASE / THREE-PHASE AUTOMATIC PANEL

Product price:

5,665.00 € tax excluded

Product description:

GENERATOR SUPERSILENCED 9,5KVA 50/60 Hz SINGLE-PHASE / THREE-PHASE AUTOMATIC PANEL

The generator single-phase / three-phase is equipped with a YANMAR 3TNV76 diesel supplied engine, capable of delivering a power of 9,5KVA with automatic starting panel.

This generator is equipped with **electric start, manual or automatic** with 12 V battery, with automatic panel and **COMAP IL4 AMF9** control unit which allows you to view all electrical parameters of the engine and generator, of the functions, states of the Generator, manage the entire group and view, in case they occur, the errors or alarms of the system. In addition, this generator is equipped with electric or automatic starting via the ATS panel, which allows it to be switched on automatically in the event of a blackout.

AUTOMATIC TRANSFER SWITCH ATS

The Generator is designed for the use of an ATS automatic transfer switch. Thanks to which you will no longer have to worry about blackouts because if it goes off the power grid this panel is able to automatically start the group and will allow you to continue your business without losing your work data.

The Generator has a low fuel consumption, in fact it consumes only 2 liters / hour at 75% of the load, combined with a large tank of 70 liters of maximum capacity, it will give you an autonomy of about 35 hours.

The generator guarantees efficient and silent operation thanks to the motor YANMAR 3TNV76



engine, which allows to deliver a maximum power of 9.5KVA.

TECHNICAL FEATURES

Type of phase: Singlephase / Threephase

Power for continuous use 50 Hz: 8.7 KVA / 7 KW

Maximum power 50 Hz: 9.5 KVA / 7.7 KW Power continuous use 60 Hz: 10 KVA / 8 KW Maximum power 60 Hz: 11 KVA / 8.8 KW

Engine: YANMAR 3TNV76
Emissions standard: Not issued
Engine revs: 1500/1800 rpm
Starting: Electric / Automatic

Fuel: Diesel

Voltage available at terminals (V): 230/400/265/460

Frequency: 50/60 Hz

Voltage regulator: COMPOUND

Socket board: 1 x CEE 16A 400V 5P / Terminal block

Tank capacity: 70 I

Autonomy at 75% of the load: 35 h Consumption at 75% of the load: 2 Lt / h Acoustic pressure: 65 dB (A) @ 7 m

Length: 1750 mm Width: 700 mm Height: 1125 mm Dry weight: 450 Kg

Are you looking for a generator with different technical characteristics? <u>HERE</u> you can find the area dedicated to specialized brand generators.

Non-binding images and technical data.

Product features:

Phase: Single phase / Three phase

Maximum power three phase (KW): 7,7 (50Hz) / 8,8 (60Hz) Continuous power three phase (KW): 7 (50Hz) / 8 (60Hz) Maximum power three phase (KVA): 9,5 (50Hz) / 11 (60Hz) Continuous power three phase (KVA): 8,7 (50Hz) / 10 (60Hz)

Fuel: Diesel

Frequency (Hz): 50 / 60

Voltage (V): 230 / 400 / 265 / 460

Engine: YANMAR 3TNV76



Engine rpm (rpm): 1500 / 1800 Speed governor: Mechanical

Starting system: Electric / Automatic

Engine capacity (cm³): 1116

Number cylinders: 3 Cylinders' position: In line

Cooling: Water

Protection degree: IP21 Fuel tank capacity (L): 70

Consumption (L/h): 2 at 75% of the load

Running time (h): 35 at 75% load

Length (mm): 1750 Width (mm): 700 Height (mm): 1125 Dry weight (Kg): 450

Silenced: Yes

Super silenced: Yes

ATS Switch device : Optional Voltage regulator: Compound