



GENERATOR SILENCED 88KVA SINGLE-PHASE/THREE-PHASE AUTOMATIC CONTROL PANEL

Product price:

10,780.00 € tax excluded

Product description:

GENERATOR SILENCED 88KVA SINGLE-PHASE/THREE-PHASE AUTOMATIC CONTROL PANEL

The generator single-phase / three-phase is equipped with a Baudouin 4M11G90/5 diesel-powered engine, capable of delivering a power of 88KVA complete with **AVR voltage regulator** and automatic control panel.

This generator is equipped with **electric**, **manual or automatic start** with 12 V battery, and is equipped with **COMAP AMF 9 NT control unit** which allows you to view all electrical parameters of the engine and generator, of the functions, status of the generator, manage the entire group and view, in case they occur, the errors or alarms of the system.

This unit is equipped with a soundproof cabin, made of 20/10 thick carbon steel, folded and electro-welded, with protection class IP23 and which can be opened in two sections. This cabin allows an incredible reduction of noise pollution, up to obtaining an acoustic pressure of only 70 dB (A) recorded at a distance of 7 meters.

The generating set guarantees efficient and silent operation thanks to the Baudouin 4M11G90/5 motor, which allows to deliver a maximum power of 88KVA. In addition, this unit is equipped with electric or automatic starting via the ATS panel, which allows it to be switched on automatically in the event of a blackout.

AUTOMATIC STARTING PANEL ATS

The generator is set up for the use of an ATS automatic starting panel. Thanks to which you will



no longer have to worry about blackouts because if it goes off the electricity grid this panel is able to automatically start the generator and will allow you to continue your business without losing your work data.

The generator control panel consists of:

- Magnetothermic switch 160 A
- Sockets: Terminal block
- Automatic control unit COMAP AMF 9 NT
- Battery charger 2,5 A
- Switching connection
- Emergency stop button

TECHNICAL FEATURES

Phase type: Single-phase / Three-phase Continuous use power: 80 KVA / 64 KW Maximum power: 88 KVA / 70.4 KW Motor: Baudouin 4M11G90 / 5

Engine revs: 1500 rpm

Emissions regulations: Not Emitted

Starting: Electric / Automatic

Fuel: Diesel

Voltage available at terminals: 230/400 V

Frequency: 50 Hz Voltage regulator: AVR

Socket panel: Terminal block

Tank capacity: 140 I

Autonomy at 75% of the load: 10.5 h

Consumption at 75% of the load: 13.3 Lt / h

Acoustic pressure: 70 dB (A) @ 7 m

Length: 2850 mm Width: 1000 mm Height: 1420 mm Weight dry: 1300 Kg

Are you looking for a generator with different technical characteristics? <u>HERE</u> you can find the area dedicated to generating sets of specialized brands.

Non-binding images and technical data.

Product features:



Phase: Single phase / Three phase

Maximum power three phase (KW): 70.4 Continuous power three phase (KW): 64 Maximum power three phase (KVA): 88 Continuous power three phase (KVA): 80

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 230 / 400

Engine: Baudouin 4M11G90/5

Emissions Regulations: Stationary Use

Engine rpm (rpm): 1500 Speed governor: Mechanical

Starting system: Electric / Automatic

Engine capacity (cm³): 4500

Number cylinders: 4 Cylinders' position: In line

Cooling: Water

Alternator: Linz PRO22S C/4

Poles: 4

Fuel tank capacity (L): 140

Consumption (L/h): 13.3 at 75% load Running time (h): 10.5 at 75% load

Length (mm): 2850 Width (mm): 1000 Height (mm): 1400 Dry weight (Kg): 1300

Silenced: Yes

Super silenced: Yes

ATS Switch device : Optional

Voltage regulator: AVR