



GENERATOR SUPER SILENCED 11KVA SINGLE PHASE / THREE PHASE AVR MANUAL PANEL

Product price:

6,140.00 € tax excluded

Product description:

GENERATOR SUPER SILENCED 11KVA SINGLE PHASE / THREE PHASE AVR MANUAL PANEL

The generator single-phase / three-phase is equipped with a Kohler KDW 1404 diesel-powered engine, capable of delivering a power of 11KVA with **AVR** voltage regulator.

This Generator is equipped with **electric start, manual** with 12 V battery, with panel and **LOVATO RGK 30** control unit that allows you to view the fuel reserve, the temperature water, oil pressure, battery voltage, belt integrity, high-low speed. In addition, it signals the enabled protections and the timing of the glow plugs

The Generator has a low fuel consumption, in fact it consumes only 2.5 liters / hour at 75% of the load, combined with a large tank of 70 liters of maximum capacity, it will give you an autonomy of about 28 hours.

The Generator guarantees efficient and silent operation thanks to the Kohler KDW 1404 engine, which allows to deliver a maximum power of 11KVA.

TECHNICAL FEATURES

Phase type: Single-phase / Three-phase Continuous use power: 10 KVA / 8 KW Maximum power: 11 KVA / 8.8 KW

Motor: Kohler KDW 1404

Emissions regulations: Not emitted

Engine revs: 1500 rpm Starting: Electric / Manual



Fuel: Diesel

Voltage available at terminals (V): 230/400

Frequency: 50 Hz

Voltage regulator: AVR

Socket panel: 1 x CEE 16A 400V 5P / CEE 16A 230V 3P

Tank capacity: 70 I

Autonomy at 75% of the load: 28 h

Consumption at 75% of the load: 2,5 Lt / h

Acoustic pressure: 62 dB (A) @ 7 m

Length: 1750 mm Width: 700 mm Height: 1125 mm Dry weight: 500 Kg

Are you looking for a generator with different technical characteristics? <u>HERE</u> you can find the area dedicated to specialized brand generators.

Non-binding images and technical data.

Product features:

Phase: Single phase / Three phase Maximum power three phase (KW): 8.8 Continuous power three phase (KW): 8 Maximum power three phase (KVA): 11 Continuous power three phase (KVA): 10

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 230 / 400 Engine: Kohler KDW 1404 Engine rpm (rpm): 1500 Speed governor: Mechanical Starting system: Electric / Manual Engine capacity (cm³): 1372

Number cylinders: 4

Cylinders' position: In line Protection degree: IP21 Fuel tank capacity (L): 70

Consumption (L/h): 2.5 al 75% del carico

Running time (h): 28 at 75% load

Length (mm): 1750



Width (mm): 700 Height (mm): 1125 Dry weight (Kg): 500

Silenced: Yes

Super silenced: Yes ATS Switch device : No Voltage regulator: AVR

