



GENERATOR SINGLE-PHASE / THREE-PHASE 15KVA AVR STAGE V

Product price:

2.506,25 € tax excluded

Product description:

GENERATOR SINGLE-PHASE / THREE-PHASE 15KVA AVR STAGEV

The generator single / three-phase is equipped with an OHV720 StageV petrol engine, capable of delivering a power of 15KVA, complete with **AVR voltage regulator**.

The Generator adapts perfectly to the most varied uses, thanks to the handling trolley that allows it to be relocated in perfect safety and simplicity. Thanks to the increased tank of 40 l, this generator has an extraordinary autonomy of 8.2 h with 75% of the load.

These generators are equipped with high quality components, light weight, compact, ease of use and also the modern design, equipped with a practical electric start.

AVR VOLTAGE REGULATOR

The Generator is supplied complete with AVR regulator. The AVR is a device that allows you to **keep the output more constant and less dependent on the load**. Thanks to the AVR there are fewer drops or peaks in current and this makes the use of the various connected devices safer, improving their performance and duration.

STAGEV EMISSIONS REGULATION

The generator is equipped with a "mobile" STAGEV motorization, as required by the European Regulation 2016/1628. These new engines make it possible to exponentially reduce the emissions of particulate matter and nitrogen oxides delivered by the generator into the environment, and ensure a reduction in the environmental impact of 200% compared to standard engines.

TECHNICAL FEATURES





Type of phase: Singlephase / Threephase
Maximum singlephase power: 13.8 KVA / 11 KW
Maximum threephase power: 15 KVA / 12 KW
Voltage: 230/400 V
Frequency: 50 Hz
Engine: OHV720
Fuel: Petrol
Engine speed: 3000 rpm
Emissions standard: StageV
Number of cylinders: 2
Displacement: 713 cc
Tank capacity: 40 l
Consumption: 4.9 l @ 75%
Autonomy: 8.2 h
Alternator: Self-excited with brushes
Configuration sockets: 2 x SCHUKO 230V - 1 x 32A 5P 400V - 1 x 12 VDC
Voltage regulator: AVR
Width: 870 mm
Length: 588 mm
Height: 726 mm
Dry weight: 184 Kg

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the full range of specialized brand generators

Non-binding images and technical data.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 11
Maximum power single phase (KVA): 13.8
Maximum power three phase (KW): 12
Maximum power three phase (KVA): 15
Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: 2 x 32A 3P 230V - 1 x 32A 5P 400V - 1 x 12 VDC
Engine: OHV720
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Starting system: Electric
Engine capacity (cm³): 713





Number cylinders: 2
Alternator: Self-excited with brushes
Fuel tank capacity (L): 40
Consumption (L/h): 4.9 l @ 75%
Running time (h): 8.2 at 75% of the load
Length (mm): 870
Width (mm): 588
Height (mm): 726
Dry weight (Kg): 184
Silenced: No
Super silenced: No
Product type: Generator
ATS Switch device : No
Voltage regulator: AVR
Engine manufacturer: Honda

