



GENERATOR SINGLE-PHASE / THREE-PHASE 15KVA AVR STAGE V

Product price:

2,055.00 € tax excluded

Product description:

GENERATOR SINGLE-PHASE / THREE-PHASE 15KVA AVR STAGEV

The generator single / three-phase is equipped with an OHV720 StageV petrol engine, capable of delivering a power of 15KVA, complete with **AVR voltage regulator**.

The Generator adapts perfectly to the most varied uses, thanks to the handling trolley that allows it to be relocated in perfect safety and simplicity. Thanks to the increased tank of 40 l, this generator has an extraordinary autonomy of 8.2 h with 75% of the load.

These generators are equipped with high quality components, light weight, compact, ease of use and also the modern design, equipped with a practical electric start.

AVR VOLTAGE REGULATOR

The Generator is supplied complete with AVR regulator. The AVR is a device that allows you to **keep the output more constant and less dependent on the load**. Thanks to the AVR there are fewer drops or peaks in current and this makes the use of the various connected devices safer, improving their performance and duration.

STAGEV EMISSIONS REGULATION

The generator is equipped with a "mobile" STAGEV motorization, as required by the European Regulation 2016/1628. These new engines make it possible to exponentially reduce the emissions of particulate matter and nitrogen oxides delivered by the generator into the environment, and ensure a reduction in the environmental impact of 200% compared to standard engines.

TECHNICAL FEATURES



Type of phase: Singlephase / Threephase

Maximum singlephase power: 13.8 KVA / 11 KW

Maximum threephase power: 15 KVA / 12 KW

Voltage: 230/400 V

Frequency: 50 Hz

Engine: OHV720

Fuel: Petrol

Engine speed: 3000 rpm

Emissions standard: StageV

Number of cylinders: 2

Displacement: 713 cc

Tank capacity: 40 l

Consumption: 4.9 l @ 75%

Autonomy: 8.2 h

Alternator: Self-excited with brushes

Configuration sockets: 2 x SCHUKO 230V - 1 x 32A 5P 400V - 1 x 12 VDC

Voltage regulator: AVR

Width: 870 mm

Length: 588 mm

Height: 726 mm

Dry weight: 184 Kg

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the full range of specialized brand generators

Non-binding images and technical data.

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 11

Maximum power single phase (KVA): 13.8

Maximum power three phase (KW): 12

Maximum power three phase (KVA): 15

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 2 x 32A 3P 230V - 1 x 32A 5P 400V - 1 x 12 VDC

Engine: OHV720

Emissions Regulations: Stage 5

Engine rpm (rpm): 3000



Starting system: Elettrico

Engine capacity (cm³): 713

Number cylinders: 2

Alternator: Autoeccitato con spazzole

Fuel tank capacity (L): 40

Consumption (L/h): 4,9 l @ 75%

Running time (h): 8.2 at 75% of the load

Length (mm): 870

Width (mm): 588

Height (mm): 726

Dry weight (Kg): 184

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : No

Voltage regulator: AVR

