



PTO Generator Single Phase 37.2 kVA/ Three Phase 93 kVA AVR

Product price:

5,900.00 € tax excluded

Product description:

PTO Generator Single Phase 37.2 kVA/ Three Phase 93 kVA AVR

- For outdoor applications (field and home), in case of blackouts and in areas not served by the power grid
- Supplied with multiplier kit and protection, support with 3-point attachment (patented design), electrical panel with multifunction digital display for real-time data reading (voltmeter, frequency meter, ammeter, hour meter)
- Durability over time and maximum protection (thermal-magnetic and differential)
- Warranty 24 months
- Easy packaging and subsequent storage

Technical Data:

Phase: Single / Three Phase

RPM: 1500

Required tractor power (Hp): 285

Single-phase power (kVA): 37.2

Three-phase power (kVA): 93

Pto Speed (rpm): 400

Voltage (V): 230 / 400

Frequency (Hz): 50

Length (mm): 1204

Width (mm): 640

Height (mm): 923

Weight (Kg): 382

AVR

Non-binding images and technical data.



Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 29

Maximum power single phase (KVA): 37.2

Maximum power three phase (KW): 74.4

Maximum power three phase (KVA): 93

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 32A 3P+N+T CEE - 1 x 230V 32A 2P+T CEE - 1 x 230V SCHUKO

Engine rpm (rpm): 1500

Protection degree: IP23

PTO speed (round/min): 400

Minimum tractor output (HP): 285

Transmission ratio: 1 : 3.8

Length (mm): 1204

Width (mm): 640

Height (mm): 923

Dry weight (Kg): 382

Brushes: No

Voltage regulator: AVR

