



# GENERATOR PTO SINGLE-PHASE / THREE- PHASE 40KVA

Product price:

**3,250.00 € tax excluded**

## Product description:

### GENERATOR PTO SINGLE-PHASE / THREE-PHASE 40KVA

Generator PTO Single / three-phase complete with LINZ PRO18ME/4 alternator capable of delivering a power of 40KVA.

The PTO generator is very reliable as it has been built and designed using high quality materials. The PTO generator is easy to transport, install and position thanks to its compact size, this model is ideal to be mounted on a tractor unit.

For correct operation, the generator needs to be connected to a tractor capable of delivering a mechanical power of at least 80 HP and a PTO speed of at least 430 rpm. The minimum parameters indicated are necessary for the correct functioning of the PTO generator, if they are not respected it can cause malfunctions or in the worst case damage to the equipment can be caused.

These compact, robust and easy-to-use generators come complete with base with 3-point hitch for secure attachment to any tractor. The generator is equipped with an IP44 panel with magnetothermic switch socket, 63A 400V socket, 32A auxiliary socket and voltmeter.

## TECHNICAL FEATURES

Phase type: Single phase / Three phase

Singlephase maximum power: 20 KVA / 16 KW

Singlephase continuous power: 23 KVA / 18.4 KW

Threephase maximum power: 40 KVA / 32 KW

Continuous power Threephase: 35 KVA / 28 KW

Voltage: 230 - 400 V

Frequency: 50 Hz

Coupler revolutions: 1500 rpm



Necessary tractor power: 80 hp  
Power take-off revolutions: 430 rpm  
Alternator: LINZ PRO18ME / 4  
N ° of poles: 4  
Insulation class: H  
Protection class: IP 23  
Voltage regulator: AVR  
Length: 1265 mm  
Width: 730 mm  
Height: 1300 mm  
Weight: 357 Kg

Are you looking for a product with different technical characteristics? [HERE](#) you can find the full range of generator PTO of specialized brands.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

#### **Product features:**

Phase: Single phase / Three phase  
Maximum power single phase (KW): 18.4  
Continuous power single phase (KW): 16  
Maximum power single phase (KVA): 23  
Continuous power single phase (KVA): 20  
Maximum power three phase (KW): 32  
Continuous power three phase (KW): 28  
Maximum power three phase (KVA): 40  
Continuous power three phase (KVA): 35  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Engine rpm (rpm): 1500  
Alternator: LINZ PRO18ME/4  
Poles: 4  
Protection degree: IP23  
PTO speed (round/min): 440  
Required tractor power: 80 Hp  
Length (mm): 1265  
Width (mm): 730  
Height (mm): 1300  
Dry weight (Kg): 357  
Silenced: No

---



Shop name

---

Super silenced: No  
Voltage regulator: AVR



---

PrestaShop