



MOSA GE 65 KSX GENERATOR 66 KVA SINGLE-PHASE / THREE- PHASE AVR

Product price:

14.940,00 € tax excluded

Product description:

MOSA GE 65 KSX GENERATOR 66 KVA SINGLE-PHASE / THREE-PHASE AVR

The MOSA GE 65 KSX single / three-phase generator is equipped with a diesel-powered Kohler KDI 2504 TM engine, and is capable of delivering a maximum power of 66 KVA.

The MOSA GE 65 KSX is equipped with **electric, manual or automatic start** with 12 V battery, and is equipped with **COMAP AMF 9 NT control unit** which allows to view all the electrical parameters of the engine and generator, the functions, the status of the generator, manage the entire group and view, in case they occur, the errors or alarms of the system.

Thanks to the AVR voltage regulator included in the supply of the group, the MOSA GE 65 KSX is able to supply "clean" current and voltage with an accuracy of less than one percent, this guarantees the user to be able to safely connect any type of electrical and electronic device.

The MOSA GE 65 KSX generator guarantees efficient and silent operation thanks to the Kohler KDI 2504 TM engine, which allows to deliver a maximum power of 66KVA.

AUTOMATIC STARTING PANEL ATS

The MOSA GE 65 KSX is set up for the use of an ATS automatic starting panel. Thanks to which you will no longer have to worry about blackouts because if it goes off the electricity grid this panel is able to automatically start the generator and will allow you to continue your business without losing your work data.

TECHNICAL FEATURES MOSA GE 65 KSX

Phase type: Single / Three phase





Singlephase maximum power: 22 KVA / 17.6 KW
Singlephase continuous power: 20 KVA / 16 KW
Threephase maximum power: 66 KVA / 52.8 KW
Threephase continuous power: 60 KVA / 48 KW
Fuel: Diesel
Voltage: 230/400 V
Frequency: 50 Hz
Motor: KOHLER KDI 3404TM
Emissions regulations: Not Emitted
Number of cylinders: 4
Engine revolutions: 1500 rpm
Starting: Electric
Voltage regulator: AVR HVR-30
Tank capacity : 100 Lt
Consumption: 11.3 Lt / h at 75% of the load
Autonomy: 8.8 h at 75% of the load
Acoustic pressure: 66 dB (A) @ 7m
Length : 2050 mm
Width: 900 mm
Height: 1420 mm
Weight: 1215 Kg

Are you looking for a product with different technical characteristics? [HERE](#) you can find the area dedicated to MOSA generators or other specialized brands.

Non-binding images and technical data.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 17.6
Continuous power single phase (KW): 16
Maximum power single phase (KVA): 22
Continuous power single phase (KVA): 20
Maximum power three phase (KW): 52.8
Continuous power three phase (KW): 48
Maximum power three phase (KVA): 66
Continuous power three phase (KVA): 60
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Engine: KOHLER KDI 3404TM
Emissions Regulations: Not Emitted





Engine rpm (rpm): 1500

Starting system: Electric

Engine capacity (cm³): 3359

Number cylinders: 4

Inyección : Direct

Alternator: Sincrono trifase, autoeccitato, autoregolato, senza spazzole

Fuel tank capacity (L): 100

Running time (h): 8.8 to 75% load

Acoustic pressure: 66 dB(A) at 7 m

Length (mm): 2050

Width (mm): 900

Height (mm): 1420

Dry weight (Kg): 1215

Product type: Generator

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Kohler

