



ECOFLOW DOUBLE-SIDED SOLAR PANEL 220W PORTABLE BATTERY CHARGING

Product price:

409.02 € tax excluded

Product description:

ECOFLOW DOUBLE-SIDED SOLAR PANEL 220W PORTABLE BATTERY CHARGING

The solar panel ECOFLOW bifacial has a 220 W primary side and a 155 W side on the back for ambient light. With this feature it captures up to 25% more solar energy and charge your portable battery even faster.

The slim one-piece tempered glass design makes it five times more durable than comparable panels; it can withstand temperatures up to 150°C.

It comes with its own carrying case so you can take it anywhere. Once it arrives at your destination, simply open it up and use it as a tripod to get the right exposure to the sun.

The 220 W EcoFlow solar panel is dust and water resistant to withstand all weather conditions, ideal for outdoor activities.

TECHNICAL FEATURES.

Front rated power: 220W

Rear rated power: 155W

Efficiency: 22% -23%

Connector type: MC4

Open circuit voltage: 21.4 V (Vmp 18.2V)

Front short circuit current: 13A (Imp 12A)

Rear short circuit current: 8.8A (Imp 8.4A)

Cell type: Monocrystalline silicon

Operating and storage temperature: -20 ° C to 85 ° C



Dimensions: 820 x 1830 x 25 mm

Weight: 9.5 kg

Looking for a product with different technical characteristics? [HERE](#) you can find the area dedicated to portable batteries or UPS units.

Images and technical data are not binding and may be subject to revision by the manufacturer.

Product features:

Nominal power continuous: 220 W

Operating temperature (°C): -20 / 85

Open size (mm): 820 x 1830 x 25

Weight (Kg): 9.5

Efficiency: 22% - 23%

