



# PRAMAC GBW10P Generator Set Three-phase MCP 9.65KVA Enclosed with manual control panel

**Product price:** 

6,366.00 € tax excluded

## **Product description:**

## PRAMAC GBW10P MCP THREE-PHASE DIESEL GENERATOR 9.65KVA

The PRAMAC GBW10P single-phase/three-phase generator is equipped with a Perkins 403D-11G diesel engine, capable of delivering a power output of 9.65 KVA, complete with a Compound voltage regulator.

The PRAMAC GBW10P generator is fitted with an electric start and a manual control panel that allows you to view all electrical parameters of the engine and generator, monitor functions and operating status, manage the entire unit, and display any errors or alarms if they occur.

The PRAMAC GBW10P comes with a soundproof canopy, made of galvanized sheet metal, bent and electro-welded, with IP23 protection rating and side doors for both ordinary and extraordinary maintenance. The generator ensures efficient and quiet operation thanks to the Perkins 403D-11G diesel engine, which delivers a maximum power output of 9.65 KVA.

# <u>Technical specifications PRAMAC GBW10P MCP:</u>

Phase type: Single-phase / Three-phase Continuous power: 8.71 KVA / 6.97 KW Maximum power: 9.65 KVA / 7.72 KW

Engine: Perkins 403D-11G Engine speed: 1500 rpm

Emissions standard: Non-certified

Starting system: Electric

Fuel: Diesel

Available terminal voltage: 230 / 400 V

Frequency: 50 Hz



Voltage regulator: Compound

Tank capacity: 50 L

Fuel consumption at 75% load: 1.98 L/h

Autonomy at 75% load: 25.76 h Noise level: 66 dB(A) @ 7 m

Length: 1645 mm Width: 870 mm Height: 1072 mm Dry weight: 460 Kg

### Sockets:

N.1 3P+N+T CEE 400V 32A N.1 3P+N+T CEE 400V 16A N.2 2P+T CEE 230V 16A N.1 230V 16A SCHUKO

Are you looking for a generator similar to the PRAMAC GBW10P MCP but with different technical specifications? <u>CLICK HERE</u> to explore our dedicated section of PRAMAC generators or other specialized brands.

### **Product features:**

Phase: Three phase

Maximum power three phase (KW): 7.72 Continuous power three phase (KW): 6.97 Maximum power three phase (KVA): 9.65 Continuous power three phase (KVA): 8.71

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 32A 3P+N+T CEE - 1 x 400V 16A 3P+N+T CEE - 2 x 230V 16A

2P+T CEE - 1 x 230V 16A SCHUKO

Engine: HONDA GC160

**Emissions Regulations: NON EMISSIONATO** 

Speed governor: Mechanical Starting system: Elettrico Engine capacity (cm³): 1131

Number cylinders: 3 Cylinders' position: In line

Oil capacity (L): 4.9 Cooling: Water

Alternator: Linz E1S13SB, with brushes

Poles: 4



Fuel tank capacity (L): 50

Consumption (L/h): 1.9 al 75% del carico Running time (h): 25 al 75% del carico

Acoustic power: 95 dB(A)

Acoustic pressure: 66 dB(A) at 7 m

Length (mm): 1645 Width (mm): 870 Height (mm): 1072 Dry weight (Kg): 460

Silenced: Yes

Super silenced: Yes Product type: Generator ATS Switch device: No

Voltage regulator: Compound Engine manufacturer: Perkins

