



PRAMAC GDW360 V SILENT GENERATOR 357.6KVA SINGLE-PHASE / THREE-PHASE AUTOMATIC PANEL

Product price:

52,456.23 € tax excluded

Product description:

PRAMAC GDW360 V SILENT GENERATOR 357.6KVA SINGLE-PHASE / THREE-PHASE AUTOMATIC PANEL

The PRAMAC GDW360 V single/ three-phase generator set is equipped with a Volvo TAD1351GE Diesel engine, capable of delivering a power of 357.6KVA complete with **AVR voltage regulator** .

The PRAMAC GDW360 V is equipped with **electric start, automatic** with 12 V battery, equipped with an ACP control unit that includes all the functions to manage the group and to display all the parameters of the generator, of the functions, status of the generator, manage the entire group and view, in case they occur, the errors or alarms of the system.

PRAMAC GDW360 V is equipped with a soundproof cabin, made of galvanized, folded and electro-welded sheet metal, with protection class IP23 with doors that can be opened for ordinary and extraordinary maintenance. The generating set guarantees efficient and silent operation thanks to the Volvo TAD1351GE Diesel engine, which allows to deliver a maximum power of 357.6KVA. In addition, this unit is equipped with electric or automatic starting via the ATS panel, which allows it to be switched on automatically in the event of a blackout.

ATS AUTOMATIC TRANSFER PANEL PREPARATION

The generator is set up for the use of an ATS automatic transfer panel. Thanks to which you will no longer have to worry about blackouts because if it goes off the electricity grid this panel is able to automatically start the generator and will allow you to continue your business without losing your work data.



TECHNICAL FEATURES PRAMAC GDW360 V

Phase type: Single-phase / Three-phase
Continuous use power: 357.6 KVA / 286.1 KW
Maximum power: 326.1 KVA / 260.9 KW
Engine: Volvo TAD1351GE
Engine revolutions: 1500 rpm
Starting: Electric / Automatic
Fuel: Diesel
Voltage available at terminals: 230/400 V
Frequency: 50 Hz
Voltage regulator: AVR
Socket panel: Terminal board
Tank capacity: 650 l
Consumption at 75% of the load: 52.41 l / h
Autonomy at 75% of the load: 12.40 h
Acoustic pressure: 68 dB (A) @ 7 m
Length: 4000 mm
Width: 1460 mm
Height: 2147 mm
Dry weight: 4015 Kg

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the area dedicated to PRAMAC generators or other specialized brands.

Non-binding images and technical data.

Product features:

Phase: Single phase / Three phase
Maximum power three phase (KW): 286.1
Continuous power three phase (KW): 260.9
Maximum power three phase (KVA): 357.6
Continuous power three phase (KVA): 326.1
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Engine: Volvo TAD1351GE
Engine rpm (rpm): 1500
Speed governor: Electronic
Starting system: Electric / Automatic



Engine capacity (cm³): 12780
Number cylinders: 6
Cylinders' position: In line
Cooling: Water
Alternator: Mecc alte ECO38 2L4 C
Poles: 4
Acoustic pressure: 68 dB(A) at 7 m
Length (mm): 4000
Width (mm): 1460
Height (mm): 2147
Dry weight (Kg): 4015
Silenced: Yes
Super silenced: Yes
ATS Switch device : Optional
Voltage regulator: AVR
Engine manufacturer: Volvo
Video: Z2r7okjr4EE