



GENERATOR SINGLE-PHASE / THREE-PHASE 30KVA AVR WITH MANUAL CONTROL PANEL

Product price:

9,842.00 € tax excluded

Product description:

GENERATOR SINGLE-PHASE / THREE-PHASE 30KVA with manual control panel

Single/three phase 30KVA generator with a 1500 rpm Perkins diesel engine, compact and easy to use, mounted on a fixed base. This generator is equipped with a sound-proofed cabin made of structural steel plate, weatherproofing and an interior lining made of sound-absorbing material with high noise reduction, which makes the supersilenced.

The generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The generator is equipped with an electric starter with a low fuel consumption battery, consuming only 5,6 litres per hour at 75% load. The fuel tank is incorporated in the crankcase for ease of use.

This generator is perfect for use outdoors, such as on construction sites.

The generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

Technical characteristics of the generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 26.4 KW / 33 KVA

Three-phase continuous power: 24 KW / 30 KVA

Maximum single-phase power: 8.8 KW / 11 KVA

Single-phase continuous use power: 8 KW / 10 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: PERKINS 1103A-33G



Engine speed: 1500 rpm
Starting: Electric
Consumption: 5.6 Lt/h at 75% load
Length: 1800 mm
Width: 850 mm
Height: 1275 mm
Weight: 855 Kg
Super-silenced
AVR

If you are looking for a product like the then you can browse the full range of [generators](#) or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW):
Continuous power single phase (KW): 8
Maximum power single phase (KVA): 11
Continuous power single phase (KVA): 10
Maximum power three phase (KW): 26.4
Continuous power three phase (KW): 24
Maximum power three phase (KVA): 33
Continuous power three phase (KVA): 30
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: 1 x 400V 63A 5P CEE - 1 x 230V 16A 3P CEE
Engine: PERKINS 1103A-33G
Emissions Regulations: Stationary Use
Engine rpm (rpm): 1500
Speed governor: Mechanical
Starting system: Elettrico
Engine capacity (cm³): 3300
Number cylinders: 3
Cooling: Water
Alternator: Brushless
Poles: 4
Protection degree: IP44
Bore x stroke (mm): 105 x 127
Fuel tank capacity (L): 100



Consumption (L/h): 5.6

Running time (h): 17.8

Acoustic pressure: 69 dB(A) at 7 m

Length (mm): 1800

Width (mm): 850

Height (mm): 1275

Dry weight (Kg): 855

AVR: Yes

Silenced: Yes

Super silenced: Yes

Product type: Generator

ATS Switch device : No

Voltage regulator: AVR

Engine manufacturer: Perkins

