

GENERATOR SINGLE-PHASE 9,7KVA SILENT ELECTRIC START

Product price:

7.290,00 € tax excluded

Product description:

NO

GENERATOR SINGLE-PHASE 9,7KVA ELECTRIC START

The generator single-phase, is equipped with a KOHLER 425-2 Diesel-supplied engine, complete with capacitor voltage regulator (**AVR optional**).

It is equipped with electric start and has a low fuel consumption, in fact it consumes only 2,5 liters/hour at 75% of the load for an autonomy of up to 8 hours of operation.

The generator is equipped with silenced casing that can be opened in two sections made of sheet 20/10, soundproofing material in class 1, internal muffler. Thanks to these devices, the generator can be considered super-silenced, with a noise emission of only 75 dB recorded at a distance of 7 meters from the source.


The generator guarantees efficient and silent operation thanks to the KOHLER KD 15440 engine, which allows to deliver a maximum power of 9.7KVA.

ATS AUTOMATIC STARTING FRAME

The generator is designed for use with an ATS automatic start-up panel. Thanks to this, you will no longer have to worry about blackouts, in the event of a power failure this panel is able to automatically turn on the generator and allow you to continue your business.

The generator control panel consists of:

- Thermomagnetic circuit breaker and isolation control
- Sockets: 1 x 16A 3P 230V / 1 x 32A 3P 230V
- ATS arrangement
- Votmeter
- Ammeter



Ø.

- Ignition switch
- Emergency stop button

TECHNICAL FEATURES

Phase Type: Single Phase Continuous Use output: 8.8 KVA / 8.8 KW Maximum output: 9.7 KVA / 9.7 KW Motor: KOHLER 425-2 Motor Speed: 3000 rpm **Emissions Standard: NOT Emitted Boosting: Electric** Fuel: Diesel Voltage: 230 V Frequency: 50 Hz Socket Frame: 1 x 16A 3P 230V / 1 x 32A 3P 230V Tank Capacity: 20 I Autonomy at 75% of load: 8 h Consumption at 75% of load: 2.5 Lt/h Acoustic pressure: 75 dB(A) @ 7 m Length: 940 mm Width: 650 mm Height: 840 mm Dry weight: 235 Kg

Are you looking for a generator with different technical characteristics? Here you can find the area dedicated to generators or other specialized brands.

Images and technical data not binding.

Product features:

Phase: Single phase Maximum power single phase (KW): 9.7 Continuous power single phase (KW): 8.8 Maximum power single phase (KVA): 9.7 Continuous power single phase (KVA): 8.8 Fuel: Diesel Frequency (Hz): 50 Voltage (V): 230 Sockets configuration: 1 x 16A 3P 230V / 1 x 32A 3P 230V Engine: Kohler KD 425/2

PrestaShop

(R)

Emissions Regulations: Stationary Use Engine rpm (rpm): 3000 Starting system: Electric Engine capacity (cm³): 954 Number cylinders: 2 Cooling: Air Alternator: LINZ E1C11MB Poles: 2 Fuel tank capacity (L): 20 Consumption (L/h): 2.5 at 75% of the load Running time (h): 8 at 75% load Acoustic pressure: 75 dB(A) at 7 m Length (mm): 940 Width (mm): 650 Height (mm): 840 Dry weight (Kg): 235 Silenced: Yes Super silenced: Yes ATS Switch device : Optional Voltage regulator: Capacitor / AVR (optional) Engine manufacturer: Kohler

Ø.