



GENSET MG 3000 I-BE GENERATOR 3 KVA SINGLE PHASE STAGE V

Product price:

619,00 € tax excluded

Product description:

GENSET MG 3000 I-BE GENERATOR 3 KVA SINGLE PHASE STAGE V

The generator GENSET MG 3000 I-BE single-phase is equipped with a Briggs & Stratton XR750 StageV petrol engine capable of delivering a power of 3 KVA with **capacitor voltage regulator**.

The GENSET MG 3000 I-BE single-phase generator provides reliable power for home, business and leisure environments. Safely powering home appliances and other electronic devices. Outdoor party power solution.

The generator is easy to install and operate, just as simple as starting and stopping thanks to the clear and intuitive controls (recoil start).

GENSET MG 3000 I-BE has a completely steel structure and a large metal tank with filling indicator. The generator guarantees efficient and silent operation thanks to the Briggs & Stratton XR750 StageV engine that allows to deliver a maximum output of 3 KVA.

GENSET MG 8000 I-BE is equipped with a "mobile" STAGEV motorization, as required by the European Regulation 2016/1628. These new engines make it possible to exponentially reduce the emissions of particulate matter and nitrogen oxides delivered by the generator into the environment, and ensure a reduction in the environmental impact of 200% compared to standard engines.

TECHNICAL FEATURES GENSET MG 3000 I-BE

Type of phase: Single phase

Maximum power: 3 KVA / 2.4 KW

Continuous power: 2.7 KVA / 2.1 KW

VAC voltage: 230 V

Frequency (Hz): 50



Starting panel: Manual with auto wrap
Engine: Briggs & Stratton XR750
Emissions standard: StageV
Revolutions per minute RPM: 3000
Fuel: Petrol
Tank capacity: 3.1 l
Consumption @ 75% load: 1.4 l / h
Autonomy @ 75% load: 2.21 h
Acoustic pressure: 72 dB (A) @ 7m
Length: 610 mm
Width: 360 mm
Height: 410 mm
Net weight: 38 Kg

Are you looking for a generator with different characteristics? [HERE](#) you can find the full range of GENSET generators or other specialized brands

Non-binding images and technical data.

Product features:

Phase: Single phase
Maximum power single phase (KW): 2.4
Continuous power single phase (KW): 2.1
Maximum power single phase (KVA): 3
Continuous power single phase (KVA): 2.7
Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230
Sockets configuration: 2 Schuko
Engine: Briggs & Stratton XR750
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Ignition: Recoil
Starting system: Manual
Engine capacity (cm³): 163
Number cylinders: 1
Cooling: Air
Protection degree: IP23
Motor insulation class: H
Fuel tank capacity (L): 3.1
Consumption (L/h): 1.4
Running time (h): 2.21





Acoustic power: 97 dB(A)
Acoustic pressure: 72 dB(A) at 7 m
Length (mm): 610
Width (mm): 360
Height (mm): 410
Dry weight (Kg): 38
Silenced: No
Super silenced: No
Product type: Generator
ATS Switch device : No
Voltage regulator: Capacitor
Engine manufacturer: Briggs&Stratton