



# PRAMAC P4000 GENERATOR 3,5 KVA SINGLE-PHASE STAGEV

Product price:

**2.560,00 € tax excluded**

## Product description:

PRAMAC P4000 GENERATOR 3,5 KVA SINGLE-PHASE STAGEV

PRAMAC P4000 single-phase generator with Yanmar L70V STAGEV Diesel engine, capable of delivering a power of 3,5 KVA, **complete with voltage regulator** Condenser **(AVR Optional)** .

The Generator adapts perfectly to the most varied uses, thanks to the handling trolley that allows it to be relocated in perfect safety and simplicity. Thanks to the increased tank of 18 l, this generator has an extraordinary autonomy of 15 h with 75% of the load.

These generators are equipped with high quality components, light weight, compact, ease of use and also the modern design, equipped with a practical electric start.

The PRAMAC P4000 generator is equipped with electric or automatic starting via the ATS panel, which allows it to be switched on automatically in the event of a blackout.

## STAGEV EMISSIONS REGULATION

The generating set is equipped with a "mobile" STAGEV motorization, as required by the European Regulation 2016/1628. These new engines make it possible to exponentially reduce the emissions of particulate matter and nitrogen oxides delivered by the generator into the environment, and ensure a reduction of the environmental impact of 200% compared to standard engines.

## ATS AUTOMATIC STARTING PANEL (OPTIONAL)

The generator is set up for the use of an ATS automatic starting panel. Thanks to which you will no longer have to worry about blackouts because if it goes off the electricity grid this panel is able to automatically start the generator and will allow you to continue your business without losing your work data.



---

## TECHNICAL CHARACTERISTICS PRAMAC P4000 :

Phase type: Single-phase

Continuous use power: 3.24 KVA / 2.92 KW

Maximum power: 3.57 KVA / 3.21 KW

Engine: Yanmar L70V

Engine speed: 3000 rpm

Emissions standard: STAGEV

Starting: Electric

Fuel: Diesel

Voltage: 230 V

Frequency: 50 Hz

Voltage regulator: Capacitor (AVR Optional )

Socket panel: 1 X SCHUKO 230V 16A | 1 X CEE 230V 16A | 1 X CEE 230V 32A

Tank capacity: 18 l

Autonomy: 15.25 h at 75% of load

Consumption: 1.18 l / h at 75% of load

Acoustic pressure: 68 dB (A) @ 7 m

Length: 800 mm

Width: 525 mm

Height: 850 mm

Dry weight: 132 Kg

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the area dedicated to PRAMAC generators or other specialized brands.

Images and technical data not binding.

### Product features:

Phase: Single phase

Maximum power single phase (KW): 3.2

Continuous power single phase (KW): 2.9

Maximum power single phase (KVA): 3.5

Continuous power single phase (KVA): 3.2

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230

Sockets configuration: 1 X SCHUKO 230V 16A | 1 X CEE 230V 16A | 1 X CEE 230V 32A

Engine: Yanmar L70V, 4 stroke

Engine rpm (rpm): 3000

Speed governor: Mechanical

Starting system: Electric





---

Engine capacity (cm<sup>3</sup>): 320  
Oil capacity (L): 1.01  
Cooling: Air  
Alternator: Brushless  
Poles: 2  
Fuel tank capacity (L): 18  
Consumption (L/h): 1.18 at 75% load  
Running time (h): 15.25 at 75% load  
Acoustic power: 96 dB(A)  
Acoustic pressure: 68 dB(A) at 7 m  
Length (mm): 800  
Width (mm): 525  
Height (mm): 850  
Dry weight (Kg): 132  
Silenced: Yes  
Super silenced: Yes  
Product type: Generator  
ATS Switch device : Optional  
Voltage regulator: Capacitor / AVR (optional)  
Engine manufacturer: Yanmar

