



PRAMAC P4000 Generator

Single-phase 3.5kVA

STAGEV

Product price:

3,233.27 € tax excluded

Product description:

PRAMAC P4000 SINGLE-PHASE GENERATOR 3.5 KVA STAGE V

The PRAMAC P4000 single-phase generator with Yanmar L70V STAGE V diesel engine delivers 3.5 KVA of power and comes with capacitor voltage regulation (optional AVR).

The generator adapts perfectly to a wide range of uses thanks to the transport kit, which allows safe and easy relocation. With its enlarged 18 L tank, this generator offers an outstanding runtime of 15 h at 75% load.

These generators feature high-quality components, are lightweight and compact, easy to use, and boast a modern design with practical electric start.

The PRAMAC P4000 generator is equipped with electric start or automatic start via an ATS panel, enabling automatic start-up in the event of a blackout.

STAGE V EMISSIONS STANDARD

The generator set is equipped with a “mobile” STAGE V engine, as required by European Regulation 2016/1628. These new engines exponentially reduce particulate and nitrogen oxide emissions released into the environment, ensuring a 200% reduction in environmental impact compared to standard engines.

AUTOMATIC TRANSFER SWITCH (ATS) START PANEL (OPTIONAL)

The generator set is prearranged for use with an Automatic Transfer Switch (ATS) panel. Thanks to this, you no longer need to worry about blackouts: if the mains power fails, the panel can automatically start the generator so you can continue your activities without losing work data.

TECHNICAL FEATURES PRAMAC P4000 Single-Phase Generator 3.5kVA:

Phase type: Single-phase



Continuous power: 3.24 KVA / 2.92 KW

Maximum power: 3.57 KVA / 3.21 KW

Engine: Yanmar L70V

Engine speed: 3000 rpm

Emissions standard: STAGE V

Starting: Electric

Fuel: Diesel

Voltage: 230 V

Frequency: 50 Hz

Voltage regulation: Capacitor (optional AVR)

Socket panel: 1 x SCHUKO 230V 16A | 1 x CEE 230V 16A | 1 x CEE 230V 32A

Tank capacity: 18 L

Autonomy: 15.25 h at 75% load

Consumption: 1.18 L/h at 75% load

Sound pressure level: 68 dB(A) @ 7 m

Length: 800 mm

Width: 525 mm

Height: 850 mm

Dry weight: 132 kg

Looking for a generator set with different technical features? [HERE](#) you can find the section dedicated to PRAMAC generator sets and other specialized brands.

Product features:

Phase: Single phase

Maximum power single phase (KW): 3.2

Continuous power single phase (KW): 2.9

Maximum power single phase (KVA): 3.5

Continuous power single phase (KVA): 3.2

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230

Sockets configuration: 1 X SCHUKO 230V 16A | 1 X CEE 230V 16A | 1 X CEE 230V 32A

Engine: Yanmar L70V, 4 stroke

Engine rpm (rpm): 3000

Speed governor: Mechanical

Starting system: Elettrico

Engine capacity (cm³): 320

Oil capacity (L): 1.01

Cooling: Air

Alternator: Brushless

Poles: 2



Fuel tank capacity (L): 18
Consumption (L/h): 1.18 at 75% load
Running time (h): 15.25 at 75% load
Acoustic power: 96 dB(A)
Acoustic pressure: 68 dB(A) at 7 m
Length (mm): 800
Width (mm): 525
Height (mm): 850
Dry weight (Kg): 132
Silenced: Yes
Super silenced: Yes
Product type: Generator
ATS Switch device : Optional
Voltage regulator: Capacitor / AVR (optional)
Engine manufacturer: Yanmar