



PRAMAC LIFTER GS/P 25 PALLET TRUCK 1185x555 WITH DIGITAL WEIGH

Product price:

1.560,00 € tax excluded

Product description:

PRAMAC LIFTER GS/P 25 PALLET TRUCK 1185x555 WITH DIGITAL WEIGH

Lifter GS/P pallet truck is a smart and robust tool you can use to weigh and transport your loads at the same time, making storage and shipping processes faster, easier and more efficient. The machine can be equipped with supplements such as printer or USB and thanks to the 4 load cells it is able to be very precise and functional; ideal for checking incoming goods, avoiding overloads and determining shipping weights.

Its large 6-digit LCD display provides accurate and precise weighing in kg and lb. Its software allows not only net / gross / tare weighing, but also unit counting, adding and counting of multiple loads. Weights are displayed in 1 kg / lb steps with an accuracy of 0.05%.

The structure is designed with a double frame consisting of a lower fork on which a counter fork is located. Both forks house two load cells that allow uniform load distribution and maintain high weighing accuracy even in the event of a collision and unbalanced load.

The machine is supplied complete with rechargeable battery and charger. The battery module guarantees 50 hours of autonomy.

TECHNICAL FEATURES LIFTER GS/P 25

Type of propulsion: Manual

Lifting: Manual

Drive system: Accompaniment Front tires: POLY.I./NYLON

Rear tires: POLY.I.

Scale type: DFW 06 XPCA

Autonomy: 50 h

Full scale accuracy: 0.05%





Battery voltage: 6 V

Nominal battery capacity: 4 Ah Track width Front: 155 mm

Rear track: 375 mm Lift height: 115 mm

Drawbar height in driving position max: 1185 mm Drawbar height in driving position min: 710 mm

Fork height lowered: 90 mm Overall length: 1596 mm Drive unit length: 411mm Overall width: 555 mm

Fork dimensions - Thickness: 60 mm Fork dimensions - Width: 180 mm

Fork length: 1185 mm Fork width: 555 mm

Clearance at mid-step: 30 mm

Storage aisle for pallet 800x1200: 2085 mm

Turning radius: 1426 mm

Capacity: 2500 kg

Mass in service with battery: 117 Kg

Are you looking for a pallet truck with different technical characteristics? HERE you can find the area dedicated to LIFTER pallet trucks or other specialized brands.

Pictures and technical data are not binding.

Product features:

Drive: Manual

Operator type: Pedestrian Load capacity (Kg): 2500

Load centre distance (mm): 600 Load axle to end forks (mm): 975

Wheel base (mm): 1250 Service weight (Kg): 117

Axle load, laden rear (Kg): 1836 Axle load, laden front (Kg): 781 Axle load, unladen front (Kg): 71 Axle load, unladen rear (Kg): 46

Tyres: front wheels: POLY.I. / NYLON

Tyres: rear wheels: POLY.I.

Diameter steering wheels (mm): 200 Width steering wheels (mm): 55





Diameter load rollers (mm): 82 Width load rollers (mm): 60 Quantity rear wheels: 2 Rear balancing axle: No Tread front (mm): 155 Tread rear (mm): 375

Height of tiller in drive position max (mm): 1185

Height lowered (mm): 90 Overall lenght (mm): 1596

Lift height (mm): 115

Lenght to face of forks (mm): 411

Overall width (mm): 555 Thickness fork (mm): 60 Width fork (mm): 180 Lenght fork (mm): 1185

Distance between fork arms (mm): 555

Ground clearance at centre of wheelbase (mm): 30

Aisle width (mm): 2085 Turning radius (mm): 1426 Lifting speed laden (strokes): 12

Lifting speed unladen (strokes): 12

Weigher: Yes