



# PRAMAC LIFTER GS/P 25 PALLET TRUCK 1185x555 WITH DIGITAL WEIGH

**Product price:**

**1.560,00 € tax excluded**

## **Product description:**

### PRAMAC LIFTER GS/P 25 PALLET TRUCK 1185x555 WITH DIGITAL WEIGH

Lifter GS/P pallet truck is a smart and robust tool you can use to weigh and transport your loads at the same time, making storage and shipping processes faster, easier and more efficient. The machine can be equipped with supplements such as printer or USB and thanks to the 4 load cells it is able to be very precise and functional; ideal for checking incoming goods, avoiding overloads and determining shipping weights.

Its large 6-digit LCD display provides accurate and precise weighing in kg and lb. Its software allows not only net / gross / tare weighing, but also unit counting, adding and counting of multiple loads. Weights are displayed in 1 kg / lb steps with an accuracy of 0.05%.

The structure is designed with a double frame consisting of a lower fork on which a counter fork is located. Both forks house two load cells that allow uniform load distribution and maintain high weighing accuracy even in the event of a collision and unbalanced load.

The machine is supplied complete with rechargeable battery and charger. The battery module guarantees 50 hours of autonomy.

## TECHNICAL FEATURES LIFTER GS/P 25

Type of propulsion: Manual  
Lifting: Manual  
Drive system: Accompaniment  
Front tires: POLY.I./NYLON  
Rear tires: POLY.I.  
Scale type: DFW 06 XPCA  
Autonomy: 50 h  
Full scale accuracy: 0.05%





Battery voltage: 6 V  
Nominal battery capacity: 4 Ah  
Track width Front: 155 mm  
Rear track: 375 mm  
Lift height: 115 mm  
Drawbar height in driving position max: 1185 mm  
Drawbar height in driving position min : 710 mm  
Fork height lowered: 90 mm  
Overall length: 1596 mm  
Drive unit length: 411mm  
Overall width: 555 mm  
Fork dimensions - Thickness: 60 mm  
Fork dimensions - Width: 180 mm  
Fork length: 1185 mm  
Fork width: 555 mm  
Clearance at mid-step: 30 mm  
Storage aisle for pallet 800x1200: 2085 mm  
Turning radius: 1426 mm  
Capacity: 2500 kg  
Mass in service with battery: 117 Kg

Are you looking for a pallet truck with different technical characteristics? [HERE](#) you can find the area dedicated to LIFTER pallet trucks or other specialized brands.

Pictures and technical data are not binding.

#### **Product features:**

Drive: Manual  
Operator type: Pedestrian  
Load capacity (Kg): 2500  
Load centre distance (mm): 600  
Load axle to end forks (mm): 975  
Wheel base (mm): 1250  
Service weight (Kg): 117  
Axle load, laden rear (Kg): 1836  
Axle load, laden front (Kg): 781  
Axle load, unladen front (Kg): 71  
Axle load, unladen rear (Kg): 46  
Tyres: front wheels: POLY.I. / NYLON  
Tyres: rear wheels: POLY.I.  
Diameter steering wheels (mm): 200  
Width steering wheels (mm): 55





Diameter load rollers (mm): 82  
Width load rollers (mm): 60  
Quantity rear wheels: 2  
Rear balancing axle: No  
Tread front (mm): 155  
Tread rear (mm): 375  
Lift height (mm): 115  
Height of tiller in drive position max (mm): 1185  
Height lowered (mm): 90  
Overall length (mm): 1596  
Length to face of forks (mm): 411  
Overall width (mm): 555  
Thickness fork (mm): 60  
Width fork (mm): 180  
Length fork (mm): 1185  
Distance between fork arms (mm): 555  
Ground clearance at centre of wheelbase (mm): 30  
Aisle width (mm): 2085  
Turning radius (mm): 1426  
Lifting speed laden (strokes): 12  
Lifting speed unladen (strokes): 12  
Weigher: Yes

