



TECNOGEN TENAK MI17TK

Product description:

The TENAX series comprises diesel generator sets, 1500 rpm water- or air-cooled, with power ratings from 5.5 to 2255 kVA max, delivering three-phase 400/230 V voltage.

Available in both open base and super-silenced versions, they are equipped with silenced version, they are equipped with Perkins, John Deere industrial engines, Iveco Aifo or Lombardini engines and alternators from world leading brands such as Leroy Somer, Stamford, Mecc Alte or Marelli.

The enclosures, designed to guarantee an excellent level of level of soundproofing and optimum engine cooling, are entirely made of hot-dip galvanised steel and subsequently painted with polyester powder, making them practically unassailable by atmospheric agents. against atmospheric agents. Due to their characteristics, these machines suitable for continuous use in the industrial sector.

industrial environment and, in the super-silenced versions, for applications with switchgear in the civil sector. They are also





available on request with different engines, including Cummins, Volvo, Deutz and including Cummins, Volvo, Deutz and Mitsubishi.

The image is purely indicative.

Product features:

Phase: Three phase

Maximum power three phase (KW): 13.2

Maximum power three phase (KVA): 16.5

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Engine: MITSUBISHI S4L261SD

Engine rpm (rpm): 1500

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 1649

Number cylinders: 4

Cooling: Water

Consumption (L/h): 3.3

Length (mm): 1500

Width (mm): 750

Height (mm): 1300

Dry weight (Kg): 400

Silenced: No

Super silenced: No

ATS Switch device : Optional

Voltage regulator: Digital AVR

Engine manufacturer: Mitsubishi

