



# GENERATOR 3KVA SINGLE PHASE STAGEV AVR ELECTRIC START

## Product description:

### GENERATOR 3KVA SINGLE PHASE STAGEV AVR ELECTRIC START

The generator is equipped with a STAGEV petrol engine, it is capable of delivering a maximum power of 3KVA, with transport trolley supplied as standard, complete with AVR voltage regulator.

The generator is characterized by lower consumption and a longer life expectancy than the petrol-powered range. Equipped with a completely steel structure and a large metal tank with filling indicator. The generator guarantees efficient and silent operation thanks to the StageV petrol engine which allows to deliver a maximum power of 3 KVA.

### STAGEV EMISSIONS REGULATION

The generator is equipped with a "mobile" STAGEV motorization, as required by the European Regulation 2016/1628. These new engines make it possible to exponentially reduce the emissions of particulate matter and nitrogen oxides delivered by the generator into the environment, and ensure a reduction in the environmental impact of 200% compared to standard engines.

### AVR VOLTAGE REGULATOR

The purpose of the AVR in a power source is to keep the output stable. And if its operation is very simple when resistive loads are powered, the situation is more complex in the case of mainly inductive loads: the delayed phase current contrasts the inductor magnetic field, causing a drop in the alternator output terminals; to compensate for the phenomenon, the AVR intervenes automatically by increasing the excitation current, until the output returns to the nominal value. If the load is instead capacitive, the current acts as a magnetizer for the inductor causing an increase in the output voltage, and the AVR intervenes by reducing the excitation current

### TECHNICAL FEATURES:



---

Phase type: Single phase  
Continuous power: 2.8 KVA / 2.8 KW  
Maximum power: 3 KVA / 3 KW  
Fuel: Petrol  
Voltage: 230 V  
Frequency: 50 Hz  
Engine: 7 HP  
Engine rpm: 3000 rpm  
Emissions standard: StageV  
Starting: Electric  
Voltage regulator: AVR  
Consumption: 1.2 Lt / h at 75% load  
Tank capacity: 15 Lt  
Autonomy: 10 h at 75% load  
Length: 600 mm  
Width: 440 mm  
Height: 440 mm  
Weight: 48.6 Kg

Are you looking for a product with different technical characteristics? [HERE](#) you can find the area dedicated to specialized brands.

The images and technical data are not binding, the color of the group may vary based on availability.

#### **Product features:**

Phase: Single phase  
Maximum power single phase (KW): 3  
Continuous power single phase (KW): 2.8  
Maximum power single phase (KVA): 3  
Continuous power single phase (KVA): 2.8  
Fuel: Gasoline  
Frequency (Hz): 50  
Voltage (V): 230  
Sockets configuration: 2 Schuko + 12 V  
Engine: 7 HP  
Emissions Regulations: Stage 5  
Engine rpm (rpm): 3000  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 212  
Number cylinders: 1  
Alternator: Synchronous self-excited, with brushes





Fuel tank capacity (L): 15

Consumption (L/h): 1.5 to 75% of the load

Running time (h): 10 to 75% of the load

Length (mm): 600

Width (mm): 440

Height (mm): 440

Dry weight (Kg): 48.6

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : No

Voltage regulator: AVR