



# GENERATOR THREE-PHASE 20,7KVA AVR STAGE V

Product price:

**3.202,50 € tax excluded**

## Product description:

### GENERATOR THREE-PHASE 20,7KVA AVR STAGE V

The generator single-phase / three-phase is equipped with an OHV1000 Stage V petrol engine, capable of delivering a power of 20.7KVA, complete with **AVR voltage regulator**.

The Generator adapts perfectly to the most varied uses, thanks to the handling trolley that allows it to be relocated in perfect safety and simplicity. Thanks to the increased tank of 65 l, this generator has an extraordinary autonomy of 6.6 h with 75% of the load.

These generators are equipped with high quality components, light weight, compact, ease of use and also the modern design, equipped with a practical electric start.

The generator alternator is synchronous, single-phase, self-excited, self-regulated, brushless with class H insulation and with AVR regulator.

The advantages of the AVR voltage regulator

The automatic voltage regulator, or AVR, allows the generator to deliver stable energy and therefore be able to connect equipment with delicate electronics such as computers, appliances, smartphones and tablets: the generator is therefore ideal for home use, camping, for hobby and free time, but also for construction sites and craftsmen.

## TECHNICAL FEATURES

Type of phase: Single-phase / Three-phase

Maximum single-phase power: 20.7 KVA / 16.5 KW

Maximum three-phase power: 20.7 KVA / 16.5KW

Voltage: 230 / 400 V

Frequency: 50 Hz





Engine: OHV1000  
Fuel: Petrol  
Engine rpm: 3000 rpm  
Emissions standard: Stage V  
Number of cylinders : 2  
Displacement: 999 cc  
Tank capacity: 65 l  
Consumption: 9.8 l @ 75%  
Autonomy: 6.6 h  
Alternator: Brushless self-excited  
Voltage regulator: AVR  
Socket configuration: 1 x schuko - 1 x 63A 3P 230V - 1 x 32A 5P 400V - 1 x 12 VDC  
Width: 970 mm  
Length: 680 mm  
Height: 955 mm  
Dry weight: 255 Kg

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the full range of specialized brand generators

Non-binding images and technical data.

#### **Product features:**

Phase: Single phase / Three phase  
Maximum power single phase (KW): 16.5  
Maximum power single phase (KVA): 20,7  
Maximum power three phase (KW): 16,5  
Maximum power three phase (KVA): 20,7  
Fuel: Gasoline  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: 1 x schuko - 1 x 63A 3P 230V - 1 x 32A 5P 400V - 1 x 12 VDC  
Engine: OHV1000  
Emissions Regulations: Stage 5  
Engine rpm (rpm): 3000  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 999  
Number cylinders: 2  
Alternator: Self-excited Brushless  
Fuel tank capacity (L): 65  
Consumption (L/h): 9.8 l @ 75%  
Running time (h): 6.6 at 75% of the load



Length (mm): 970  
Width (mm): 680  
Height (mm): 955  
Dry weight (Kg): 255  
Silenced: No  
Super silenced: No  
Product type: Generator  
ATS Switch device : No  
Voltage regulator: AVR