



CGM 2000S GENERATOR 2,2KVA SINGLE PHASE STAGEV AVR

Product price:

225,00 € tax excluded

Product description:

CGM 2000S GENERATOR 2,2KVA SINGLE PHASE STAGEV AVR

The CGM 2000S single-phase generator is equipped with a STAGEV petrol engine, capable of delivering a maximum power of 2.2KVA, complete with AVR voltage regulator.

The CGM 2000S is characterized by lower consumption and a longer life expectancy than the petrol-powered range. Equipped with a completely steel structure and a large metal tank with filling indicator. The generator guarantees efficient and silent operation thanks to the StageV petrol engine which allows for the delivery of a maximum power of 2.2 KVA.

STAGEV EMISSION REGULATIONS

The CGM 2000S is equipped with a "mobile" STAGEV engine, as required by European Regulation 2016/1628. These new engines make it possible to exponentially reduce the particulate and nitrogen oxide emissions released by the generator into the environment, and guarantee a 200% reduction in environmental impact compared to standard engines.

AVR VOLTAGE REGULATOR

The purpose of the AVR, in a current generator, is to keep the output stable. And if its operation is very simple when resistive loads are powered, the situation is more complex in the case of predominantly inductive loads: the delayed phase-shifted current contrasts the inductor magnetic field, causing a drop in the alternator output terminals; to compensate the phenomenon, the AVR intervenes automatically by increasing the excitation current, until the output returns to the nominal value. If the load is instead capacitive, the current acts as a magnet for the inductor causing an increase in the output voltage, and the AVR intervenes by reducing the excitation current

TECHNICAL SPECIFICATIONS CGM 2000S:



Phase type: Single-phase
Continuous power: 2 KVA / 2 KW
Maximum power: 2.2 KVA / 2.2 KW
Fuel: Petrol
Voltage: 230 V
Frequency: 50 Hz
Engine: 7 HP
Engine speed: 3000 rpm
Emissions standard: StageV
Starter: Manual recoil
Regulator voltage: AVR
Consumption: 1.5 Lt/h at 75% of the load
Tank capacity: 15 Lt
Autonomy: 10 h at 75% of the load
Length: 600 mmWidth: 440 mm
Height: 440 mm
Weight: 37.6 Kg

Are you looking for a product with different technical characteristics? [HERE](#) you can find the area dedicated to CGM generators or other specialized brands.

The images and technical data are not binding, the color of the groupset may vary based on availability.

Product features:

Phase: Single phase
Maximum power single phase (KW): 2
Continuous power single phase (KW): 2.2
Maximum power single phase (KVA): 2
Continuous power single phase (KVA): 2.2
Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230
Sockets configuration: 2 Schuko + 12 V
Engine: 7 HP
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Starting system: Manual recoil
Engine capacity (cm³): 212
Number cylinders: 1
Alternator: Synchronous self-excited, with brushes
Fuel tank capacity (L): 15



Consumption (L/h): 1.5 to 75% of the load

Running time (h): 10 to 75% of the load

Length (mm): 600

Width (mm): 440

Height (mm): 440

Dry weight (Kg): 37,6

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : No

Voltage regulator: AVR