



# GENERATOR SILENCED 350 KVA WITH AUTOMATIC CONTROL PANEL



L'immagine è puramente a titolo dimostrativo  
The image is only for demonstration purposes

## Product description:

### **Single/three-phase 350KVA generator super-silenced with automatic control panel**

Single/three phase 350KVA generator with a 1500 rpm FPT diesel engine, compact and easy to use, mounted on a fixed base. This generator is equipped with a soundproofed cabin made of structural steel plate, weatherproofing and an interior lining made of soundproofing material with high noise reduction, which makes it supersilenced.

This generator has a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. It is equipped with an electric starter with a low fuel consumption battery, consuming only 55 litres per hour at 75% load. It also has a control panel with automatic control unit and terminal box for automatic start-up.

This generator is perfect for use outdoors, such as on construction sites.

## Technical characteristics of the generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 308 KW / 385 KVA

Three-phase continuous power: 280 KW / 350 KVA

Maximum single-phase power: 102.67 KW / 128.33 KVA

Single-phase continuous use power: 93.33 KW / 116.67 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: FPT CURSOR13 TE2A

Engine speed: 1500 rpm

Starting: Electric

Consumption: 55 Lt/h at 75% load

Length: 4300 mm

Width: 1750 mm

Height: 2350 mm



Weight: 4140 Kg  
Super-silenced  
AVR

If you are looking for a product like this then you can browse the full range of CGM [generators](#) or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

#### **Product features:**

Phase: Single phase / Three phase  
Maximum power single phase (KW): 102.67  
Continuous power single phase (KW): 93.33  
Maximum power single phase (KVA): 128.3  
Continuous power single phase (KVA): 116.67  
Maximum power three phase (KW): 308  
Continuous power three phase (KW): 280  
Maximum power three phase (KVA): 385  
Continuous power three phase (KVA): 350  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: Terminal box  
Engine: FPT (IVECO) CURSOR 13TE2A turbo  
Emissions Regulations: Stage 2  
Engine rpm (rpm): 1500  
Speed governor: Electronic  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 12880  
Number cylinders: 6  
Cooling: Water  
Alternator: Brushless  
Poles: 4  
Protection degree: IP44  
Bore x stroke (mm): 135 x 150  
Fuel tank capacity (L): 400  
Consumption (L/h): 55  
Running time (h): 7.3  
Acoustic pressure: 69 dB(A) at 7 m  
Length (mm): 4300  
Width (mm): 1750  
Height (mm): 2350



Dry weight (Kg): 4140

AVR: Yes

Silenced: Yes

Super silenced: Yes

Product type: Generator

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: FPT Iveco

