



GENERATOR SINGLE- PHASE THREE-PHASE 7KVA AVR

Product price:

1.125,00 € tax excluded

Product description:

GENERATOR SINGLE-PHASE THREE-PHASE 7KVA AVR

The Generator Single-Phase Three-Phase 7KVA 5,6KW **AVR** is with **powered by petrol** equipped with electric and manual starting, handles and wheels to carry it easily; it is a Generator Single-Phase Three-Phase 7KVA that meets a high quality standard and guarantees a high level of reliability. The whole range of Generator Single-Phase Three-Phase 7KVA has positively passed different tests for each component of which the groups and the final product are composed.

The strengths of Generator Single-Phase Three-Phase 7KVA are: the high quality of components, lightness, compactness, ease of use and also modern design. The Single-Phase Three-Phase generator is equipped with a manual recoil starting system.

The Single-Phase Three-Phase generator is equipped with a comfortable **counter**, **larger tank** for a great autonomy and **rain protection**, to use it also in case of bad weather.

The advantages of AVR voltage regulator

The automatic voltage regulator, or AVR, allows the Single-Phase Three-Phase generator 7KVA to deliver stable energy and thus be able to connect equipment with delicate electronics such as computers, appliances, smartphones and tablets: the unit set is therefore ideal for home use, camping, hobby and leisure, but also for construction sites and craftsmen.

Technical Features

Maximum Power Three Phase: 5.6KW

Maximum Power Three Phase: 7 KVA

Maximum Power Single Phase: 1.87KW

Maximum Power Single Phase: 2.33 KVA



Fuel: Gasoline
Voltage: 230 V / 400 V
Frequency: 50 Hz
Motor: 14. 0HP
Starting: Manual / Electrical
Consumption: 1.8 Lt/h at 75% load
Length: 717 mm
Width: 545 mm
Height: 592 mm
Weight: 70 Kg
Voltage regulator: AVR

Discover the full range of Industrial and portable current generators in the dedicated section.

Images and technical data not binding.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 1.8
Maximum power single phase (KVA): 2.3
Maximum power three phase (KW): 5.6
Maximum power three phase (KVA): 7
Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: 1 x 400V - 1 x 230V
Emissions Regulations: Stationary Use
Engine rpm (rpm): 3000
Starting system: Manual / Electric
Engine capacity (cm³): 420
Number cylinders: 1
Alternator: Copper
Fuel tank capacity (L): 25
Consumption (L/h): 1.8
Running time (h): 13.89
Acoustic pressure: 70 dB(A) at 7 m
Length (mm): 717
Width (mm): 545
Height (mm): 592
Dry weight (Kg): 70
Silenced: No
Super silenced: No



Product type: Generator
ATS Switch device : No
Voltage regulator: AVR