



GENERATOR SINGLE-PHASE THREE-PHASE 7KVA AVR

Product price:

1,125.00 € tax excluded

Product description:

GENERATOR SINGLE-PHASE THREE-PHASE 7KVA AVR

The Generator Single-Phase Three-Phase 7KVA 5,6KW **AVR** is with **powered by petrol** equipped with electric and manual starting, handles and wheels to carry it easily; it is a Generator Single-Phase Three-Phase 7KVA that meets a high quality standard and guarantees a high level of reliability. The whole range of Generator Single-Phase Three-Phase 7KVA has positively passed different tests for each component of which the groups and the final product are composed.

The strengths of Generator Single-Phase Three-Phase 7KVA are: the high quality of components, lightness, compactness, ease of use and also modern design. The Single-Phase Three-Phase generator is equipped with a manual recoil starting system.

The Single-Phase Three-Phase generator is equipped with a comfortable **counter**, **larger tank** for a great autonomy and **rain protection**, to use it also in case of bad weather.

The advantages of AVR voltage regulator

The automatic voltage regulator, or AVR, allows the Single-Phase Three-Phase generator 7KVA to deliver stable energy and thus be able to connect equipment with delicate electronics such as computers, appliances, smartphones and tablets: the unit set is therefore ideal for home use, camping, hobby and leisure, but also for construction sites and craftsmen.

Technical Features

Maximum Power Three Phase: 5.6KW Maximum Power Three Phase: 7 KVA Maximum Power Single Phase: 1.87KW Maximum Power Single Phase: 2.33 KVA



Fuel: Gasoline

Voltage: 230 V / 400 V Frequency: 50 Hz

Motor: 14. 0HP

Starting: Manual / Electrical

Consumption: 1.8 Lt/h at 75% load

Length: 717 mm Width: 545 mm Height: 592 mm Weight: 70 Kg

Voltage regulator: AVR

Discover the full range of <u>Industrial and portable current generators</u> in the dedicated section.

Images and technical data not binding.

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 1.8 Maximum power single phase (KVA): 2.3 Maximum power three phase (KW): 5.6 Maximum power three phase (KVA): 7

Fuel: Gasoline Frequency (Hz): 50 Voltage (V): 230 / 400

Sockets configuration: 1 x 400V - 1 x 230V Emissions Regulations: Stationary Use

Engine rpm (rpm): 3000

Starting system: Manual / Electric

Engine capacity (cm³): 420

Number cylinders: 1 Alternator: Copper

Fuel tank capacity (L): 25 Consumption (L/h): 1.8 Running time (h): 13.89

Acoustic pressure: 70 dB(A) at 7 m

Length (mm): 717 Width (mm): 545 Height (mm): 592 Dry weight (Kg): 70

Silenced: No

Super silenced: No



Product type: Generator ATS Switch device: No Voltage regulator: AVR

