



# PRAMAC P15000 Generator 12KW Single- Phase STAGEV



Product price:

**7,007.67 € tax excluded**

## Product description:

### PRAMAC P15000 GENERATOR 12KW SINGLE-PHASE STAGE V

The PRAMAC P15000 single-phase generator is equipped with a Stage V Honda GX690 petrol engine, capable of delivering a power output of 12 kW, complete with a capacitor voltage regulator. The generator is easy to install and operate, with simple starting and stopping thanks to clear and intuitive controls, and it is fitted with an automatic shutdown function in case of low oil level.

The PRAMAC P15000 can be supplied with or without AVR.

The strengths of this generator include: high-quality components, light weight, compact size, ease of use, and modern design. It features an electric start and has been specifically developed to be practical to transport under any circumstances.

The PRAMAC P15000 generator is fitted with a 40-litre tank and offers incredibly low fuel consumption, only 6 l/h, guaranteeing an autonomy of approximately 6 hours of operation. It is equipped with a digital control unit and generator protection system.

## CONTROL SECTION

- CONTROL UNIT with 3-position key: OFF, ON local start, REM remote start
- 2-wire remote start/stop (REM)
- Connector for RSS panel (available as an accessory)
- Alarm buzzer

## CONTROL PANEL

- Display: LCD with icons (52x35 mm)
- Group parameters: V - Hz - RPM - A (single-phase) - kVA - kWe - Fuel level (%)
- Parameter control and/or firmware transfer via NFC smart connection

## STAGE V EMISSION STANDARD



The PRAMAC P15000 is equipped with a Stage V "mobile" engine, in compliance with European Regulation 2016/1628. These new engines drastically reduce particulate matter and nitrogen oxide emissions released into the environment by the generator, ensuring a 200% reduction in environmental impact compared to standard engines.

### **TECHNICAL SPECIFICATIONS PRAMAC P15000:**

Phase Type: Single-phase

Continuous Power: 11.8 kVA / 10.7 kW

Maximum Power: 13.3 kVA / 12 kW

Voltage (VAC): 230 V

Frequency (Hz): 50

Voltage Regulator: Capacitor

Starting: Electric

Engine: Honda GX690

Speed (RPM): 3000

Emission Standard: Stage V

Fuel: Gasoline

Socket Panel: 1 x Schuko 230V 16A - 1 x CEE 230V 16A 2P - 1 x CEE 230V 32A 2P

Fuel Tank Capacity: 40 L

Fuel Consumption @ 75% Load: 6.11 L/h

Runtime @ 50% Load: 6.55 h

Sound Pressure: 64 dB(A) @ 7 m

Length: 1205 mm

Width: 754 mm

Height: 1035 mm

Net Weight: 288 kg

Looking for a generator with different technical specifications? [CLICK HERE](#) to explore the dedicated area for ECOGREEN generators or other specialized brands.

### **Product features:**

Phase: Single phase

Maximum power single phase (KW): 12

Continuous power single phase (KW): 10.7

Maximum power single phase (KVA): 13.3

Continuous power single phase (KVA): 11.8

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230

Sockets configuration: 1x Schuko 230V 16A IP68; 1x CEE 230V 16A 2P+T IP67; 2x CEE 230V



32A 2P+T IP67

Emissions Regulations: Stage 5

Engine rpm (rpm): 3000

Speed governor: Mechanical

Starting system: Elettrico

Oil capacity (L): 1.9

Cooling: Air

Alternator: Brushless

Poles: 2

Fuel tank capacity (L): 40

Acoustic power: 92 dB(A)

Acoustic pressure: 64 dB(A) at 7 m

Silenced: Yes

Super silenced: Yes

Product type: Generator

ATS Switch device : Optional

Voltage regulator: AVR (optional)

Engine manufacturer: Honda

