



Shop name



PRAMAC GSW560V SILENCED AUTOMATIC PANEL

Product price:

66,412.39 € tax excluded

Product description:

PRAMAC GSW560V ENCLOSED GENERATOR SET WITH AUTOMATIC CONTROL PANEL

Available in a wide range of models, the GSW series offers many solutions to a variety of applications, from continuous to emergency mains operation.

Compliant with safety and noise regulations, these gensets can be used in both residential and industrial applications.

Various control panel solutions, supplements and accessories make GSW gensets versatile and capable of meeting the most demanding customer requirements.

Technical data of the Pramac GSW560V Silent genset:

Maximum three-phase power: 448.4 KW / 560.5 KVA

Three-phase continuous power: 407.6 KW / 509.5 KVA

Fuel: Diesel

Voltage: 400 V

Frequency: 50 Hz

Engine: Volvo TAD1651GE

Starter: Electric



Consumption: 81.22 Lt/h at 75%, 103.94 Lt/h at 100% load

Length: 4500 mm

Width: 1590 mm

Height: 2347 mm

Weight: 4684 Kg

AVR

ENCLOSURE VERSION

- Enclosure made of modular galvanised steel panels suitably treated

to resist corrosion and aggressive environmental conditions

- High-quality soundproofing materials and residential muffler guarantee excellent

soundproofing performance and a low level of noise emission

- Large side doors for easy access for service and maintenance work

- Doors equipped with lockable handles

- Base frame with welded steel profiles

- Appropriately dimensioned anti-vibration mounts

- Removable support feet

- Lifting eyebolt



- Rotating parts protected against accidental contact
- Accessible earthing point

Images are purely indicative.

Translated with www.DeepL.com/Translator (free version)

Product features:

Phase: Three phase

Maximum power three phase (KW): 448.4

Continuous power three phase (KW): 407.6

Maximum power three phase (KVA): 560.5

Continuous power three phase (KVA): 509.5

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Engine: VOLVO TAD1651GE

Emissions Regulations: Stage 3A

Speed governor: Electronic

Starting system: Electric

Engine capacity (cm³): 16120

Number cylinders: 6

Cylinders' position: In line

Oil capacity (L): 34

Cooling: Water

Alternator: Mecc Alte ECO40-1L/4, brushless

Poles: 4

Fuel tank capacity (L): 650

Consumption (L/h): 81.22 at 75% of the load

Running time (h): 8 at 75% of the load

Length (mm): 4500

Width (mm): 1590

Height (mm): 2347

Dry weight (Kg): 4684

Silenced: Yes

Super silenced: No

ATS Switch device : Optional



Shop name

Voltage regulator: AVR

Engine manufacturer: Volvo



PrestaShop