



HONDA GX200 SXE5 Gasoline Engine 4.4 HP

Product description:

HONDA GX200 SXE5 Gasoline Engine 4.4 HP

HONDA GX200 SXE5 engines are recommended for a wide range of professional machines in the fields of construction, agricultural machinery, power generators, power welders, motor pumps, and other industrial applications.

TECHNICAL SPECIFICATIONS HONDA GX200 SXE5

Engine type: OHV horizontal shaft, eight cycle, 4-stroke

Number of cylinders: 1

Cylinder Arrangement: 25° inclined

Bore x stroke: 68 x 54 mm

Displacement: 196 cm³

Cooling: Forced air

Compression ratio: 8.5 : 1

Net power: 4.1 kW (5.5 HP) / 3 600 rpm

Continuous rated power 3000 rpm: 3.3 kW (4.4 HP)

Continuous rated power 3600 rpm: 3.7 kW (5.0 HP) / 3 600 rpm

Maximum torque: 12.4 Nm / 1.26 kgfm / 2 500 rpm

Ignition: Contactless transistor

Starting: Recoil with recoil starter

Fuel tank capacity: 3.1 liters

Fuel consumption at rated power: 1.7 Liters/hour - 3 600 rpm

Oil pan capacity: 0.6 Liters

Length: 313 mm

Width: 376 mm

Height: 346 mm

Net Weight: 16 kg





Looking for an engine with different technical characteristics? HERE you can find the area dedicated to HONDA engines or other specialized brands.

Images and technical data are not binding and may be subject to revision.

Product features:

Fuel: Gasoline

Engine: OHV horizontal shaft, eight cycle, 4-stroke

Ignition: A transistor contactless

Starting system: Manual

Engine capacity (cm³): 196

Number cylinders: 1

Cylinders' position: Inclined to 25°

Oil capacity (L): 0.6

Cooling: Forced air

Bore x stroke (mm): 68 x 54

Compression ratio: 8.5 : 1

Net power (kW): 4.1

Nominal power continuous: 3.3 KW (4.4 HP) / 3000 rpm - 3.7 KW (5.0 HP) / 3600 rpm

Maximum torque: 12.4 Nm / 1.26 kgfm / 2500 rpm

Fuel tank capacity (L): 3.1

Consumption (L/h): 1.7

Running time (h): 1.82

Length (mm): 321

Width (mm): 376

Height (mm): 346

Dry weight (Kg): 16.1

Engine manufacturer: Honda