



ITALTOWER FENIX PRO15 LIGHTING TOWER 4x320 W MULTILED WITH SLOW TROLLEY AND GENERATOR

Product price:

7.934,00 € tax excluded

Product description:

ITALTOWER FENIX PRO15 LIGHTING TOWER 4x320 W MULTILED WITH SLOW TROLLEY

ITALTOWER FENIX PRO15 lighting tower with Kohler 15KD350 StageV diesel engine, equipped with slow towing and manual lifting system with 4 multi-LED 320W projectors.

Italtower Fenix ??PRO15 is the perfect solution for you. a highly efficient light tower designed to provide illumination in large or outdoor work areas, such as construction sites, sports fields, storage areas and large outdoor events. This model is the perfect choice. equipped with four powerful multiled lamps of 320 W each, which provide an intense and uniform light, guaranteeing excellent visibility. optimal even in low light conditions.

The Italtower Fenix ??PRO15 equipped with **electric start** with 12 V battery, and is equipped with an electric start. equipped with **DeepSea 3110** control unit which allows you to view all the electrical parameters of the engine and generator, the functions, the status of the gen set, manage the entire group and view, if any , errors or system alarms.

The compact design and slow carriage of Italtower Fenix ??PRO15 allow you to easily move the lighting tower to different positions, without compromising its stability; or security. In addition, the built-in STAGEV generator provides outstanding energy efficiency and long-term operating range, without the need for a generator. an external power source.

STAGEV EMISSION REGULATIONS

The generator set is ready for use. equipped with a "mobile" STAGEV engine, as required by European Regulation 2016/1628. These new engines make it possible to exponentially reduce





the emissions of particulate matter and nitrogen oxides supplied by the generator into the environment, and guarantee a 200% reduction in environmental impact compared to standard engines.

TECHNICAL FEATURES OF ITALTOWER FENIX PRO15

Number of lights: 4
Lamps power: 320 W LED
Lumen: 166000 lm
Illuminated area: 5000 m²
Phase type: Single phase
Maximum power: 4.2 KW
Voltage: 230 V
Frequency: 50 Hz
Control unit: Deep Sea 3110
Engine: Kohler 15KD350
Fuel: Diesel
Revolutions: 3000 rpm
Refrigerant: Air
Emissions standard: Stage V
Alternator: Linz Alumen
Capacity; tank: 40 l
Autonomy: 72 h
Consumption: 0.55 l/h
Maximum height: 8.5 m
Lifting system: Manual
Rotation: 350°
Wind resistance: 110 Km/h
Acoustic pressure: 70 dB(A) @ 7 m
Carriage: Slow tow cart
Stabilizers 4 + 1 (wheels)
Closed dimensions (LxWxH): 1120 x 1200 x 2430 mm
Dry weight: 620 Kg

Are you looking for a product with different characteristics? [HERE](#) you can find the entire range of ITALTOWER towers or other specialized brands.

The images and technical data are not binding and may be subject to revisions by the manufacturer

Product features:

Phase: Single phase





Maximum power single phase (KW): 4.2
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230
Engine: Kohler 15KD350
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Number cylinders: 1
Cooling: Air
Alternator: Linz Alumen SB
Poles: 4
Type of lamps: LED
Lamps: 4 x 320 W
Telescopic pole: Vertical
Illuminated area (m²): 5000
Total lumens (Lm): 166000
Lifting System: Manual lifting system
Maximum height (m): 8.5
Mast rotation: 350°
Closed size (mm): 1120 x 1200 x 2430
With generator / Without generator: With generator
Transportability: Slow Trailer
Stability to wind (Km/h): 110
Fuel tank capacity (L): 40
Consumption (L/h): 0.55
Running time (h): 72
Acoustic pressure: 65 dB(A) at 7.5 m
Engine manufacturer: Kohler
Weight (Kg): 620