



OSMOSEA NEW12 150C NAUTICAL WATERMAKER 150 LT/H

Product price:

11.115,00 € tax excluded

Product description:

OSMOSEA NEW12 150C NAUTICAL WATERMAKER 150 LT/H

Watermaker Osmosea New12-150C Nautical is a one-piece reverse osmosis plant equipped with 1 carbon 4040 vessel, capable of supplying up to 150 lt/h of fresh water through the reverse osmosis process.

The watermaker's semipermeable membrane used in the reverse osmosis process separates the salt and impurities in the seawater from the freshwater, allowing the freshwater to be collected on the opposite side of the membrane.

The Osmosea New12-150C nautical watermaker is specially designed for boats, offering constant production of fresh water thanks to its automatic control system, which regulates pressure and pump speed.

Versatility is one of the key features of the Osmea New12 150C. Due to its high production capacity, it is suitable for a wide range of applications, including luxury yachts, commercial boats, and sports activity boats. It can easily provide fresh water for cooking, showers, washing and other daily needs.

Reliability and durability are key features of the Osmea New12 150C. Constructed of high-quality, corrosion-resistant materials, it is designed to withstand demanding marine conditions, ensuring long life and consistent performance over time. It requires minimal maintenance and offers reliable operation even in adverse marine conditions.

The watermaker is sold complete with:

- Osmosea® Pressure Intensifier
- Stainless Steel Feed Pump with Brushless Motor
- Pre-filter





- Post-filter:
- Flushing System
- · Carbon Filter for Flushing
- Touchscreen Remote Panel
- Digital System Control Unit
- Brushless Motor Control Unit
- Installation Kit (Hoses, fittings, hose clamps)
- Maintenance Kit (No.1 spare filter set, filter wrench, Products for washing and winterization)
- Non-Return Valve
- NMEA 2000 Compatibility

Its compact design allows easy installation on board, optimizing the use of available space on the boat. In addition, it is equipped with an intuitive control panel that allows quick and easy management of desalination operations.

The Osmosea New12-150C watermaker's control system constantly monitors the quality of the water produced, ensuring that it is of high quality and potable. The Osmosea New12-150C watermaker is also compact and easy to install, suitable for any vessel, large or small, and requires little in the way of maintenance.

REMOTE PANEL FUNCTIONS

- Start/Stop
- · Start with Soft Start
- Automatic Stop with timer or with programmable liter counter
- Inlet Pressure Readout
- Differential pressure reading
- Readout It/h produced
- Salinity reading
- Hour counter
- Immediate osmotic membrane flushing
- Osmotic membrane flushing Periodic
- Automatic Pressure Regulation
- Salinity Monitoring and Control System

TECHNICAL CHARACTERISTICS OSMOSEA NEW12 150C

Production: 150 lt/h

Daily Production: 3600 lt/day

Vessel Number: 2

Vessel Type: 4021 in Carbon Membranes: high efficiency

Expelled Salt: 99.4%

Pressure regulation: Automatic

Salinity monitoring: Automatic Electronic





Maximum use salinity: 50000 ppm Power supply voltage: 24Vdc / 230Vac

Installed power Vdc: 600 W Installed power Vac: 750 W

Frame: stainless steel

Length: 796 mm Width: 317 mm Height: 408 mm Net weight: 65 kg

Looking for a watermaker with different features? HERE you can find the area dedicated to watermakers from OSMOSEA or other specialized brands.

Non-binding images and technical data.

Product features:

Length (mm): 796 Width (mm): 317 Height (mm): 408

Feed Type: 24 VDC or 230 VAC

Production for hour at 25°C (Lt/h): 150 Daily production at 25°C (Lt/day): 3600

Membranes: n.2 4" x 21"

Remote panel: Digital touch screen

Product type: Watermaker

Weight (Kg): 65

