



# SEMITRASH MOTORPUMP DIRTY WATER 1100 l/min

Product price:

**440,00 € tax excluded**

## Product description:

### SEMITRASH MOTORPUMP SELFPRIMING FOR DIRTY WATER

The Motorpump **SEMITRASH** is a selfpriming gasoline powered with a maximum **flow rate of 1100Lt/min** with air cooling suitable for any **dirty water** application.

The selfpriming motor pump is suitable for dirtywater and slush with a solidity percentage of up to 50%. Used on construction sites, in emergency road repairs for heavy mud, also could be used as cleanwater.

The SEMITRASH engine has a cast iron cylinder barrel with excellent performance and highly reliable semi-professional quality, easy to start, ensures low noise and vibration with low consumption. Thanks to its only 35 Kg and to the trolley equipped with wheels it is possible to re-launch it easily and effortlessly wherever it is needed.

The selfpriming motorpump has a maximum flow rate of 1100Lt/min which makes it incredibly efficient due to its small and handy dimensions.

The **selfpriming motorpump** with a flow rate of 1100Lt/min is part of a type of hydraulic centrifugal with over-beam installation. Therefore, like all such types of machines, it sucks in a higher level of the liquid to be pumped and therefore needs adequate priming in order to function correctly.

The **selfpriming** is the ability to suck in the air contained in the suction pipe during the starting phase of the motorpump.

Once the motorpump has been installed and before its first start, the pump body must be filled with water through a special upper door.

Then the motorpump is put into operation; the rotating movement of the impeller creates a strong





turbulence in the liquid contained inside the pump body that generates a depression (up to 0.8 bar) inside the pipe that sucks in the air contained in it.

## TECHNICAL CHARACTERISTICS SEMITRASH

Engine: R210

Type: 4-stroke, air-cooled

Fuel: Gasoline

Cylindrance: 212ml

Tank capacity: 3.6 liters

Autonomy: 1.5 hours

Aspiration: 80 (3")

Shipment: 80 (3")

Suction capacity: 7 m

Maximum head: 26 m

Maximum capacity: 1100Lt/min

Length: 552 mm

Width: 432 mm

Height: 450 mm

Weight: 35 Kg

Are you looking for a product with different characteristics or with a flow rate greater than 1100Lt/min? Here you can find the full range of diesel and gasoline motorpumps or other specialized brands.

The images and technical data of the black water motorpump are not binding and may be subject to revision by the supplier

.

### Product features:

Fuel: Gasoline

Starting system: Pull starter

Pump type: Lightweight Pump

Fluid type: Slightly sandy wastewaters

Height of suction (m): 26

Maximum output capacity (Lt/min): 1100

Inlet diameter thread type (mm/inches): 80 mm - 3"

Outlet diameter thread type (mm/inches): 80 mm - 3"

Fuel tank capacity (L): 3.6

Length (mm): 552

Width (mm): 432





Height (mm): 450  
Dry weight (Kg): 35