



# VISA P14SG GENERATOR 14KVA SINGLE/THREE PHASE AVR



**Product price:**

**8,900.00 € tax excluded**

## **Product description:**

### **VISA P14SG GENERATOR 14KVA SINGLE/THREE PHASE AVR**

The VISA P14SG single-phase/ three-phase Generator is equipped with a Perkins 403A-15G1 Diesel engine, and is capable of delivering a maximum power of 14 KVA, complete with AVR voltage regulator.

The VVISA P14SG Generator is equipped with electric start, manual or automatic with 12 V battery, and is equipped with Comap AMF 25 control unit that allows to display of all the electrical parameters of the engine and generator, functions, states of the generator set, manage the set entirely and display, in case they occur, the errors or alarms of the system.

The Visa P14SG genset is designed for easy operation and maintenance. It also has automatic start-up and shutdown functions to simplify daily use.

Safety is a priority in the design of the Visa P14SG genset. It is equipped with protective devices such as thermal and thermal-magnetic circuit breakers to ensure safe operation and prevent damage caused by overloads or short circuits.

Thanks to the AVR voltage regulator included with the genset, the VISA P14SG is able to deliver "clean" current and voltage with an accuracy of less than one percent, this guarantees the user, to be able to safely connect all kinds of electrical and electronic devices. The VISA P14SG genset guarantees efficient and quiet operation thanks to the Perkins 403A-15G1 Engine motor, which allows it to deliver a maximum power of 14 KVA.

The versatility of the Visa P14SG is another of its strengths. It can be used in a variety of settings, such as homes, stores, farms, construction sites and more. Its ability to operate in both single-phase and three-phase modes allows it to adapt to different power supply needs.

The Visa P14SG Generator comes complete with:



- Differential Circuit Breaker;
- Liquid collection tank with level sensor;
- Motor heater;
- Oil extraction pump

### **ATS AUTHOMATIC TRANSFER SWITCH (OPTIONAL)**

The Generator is prepared for the use of Authomatic Transfer Switch ATS. Thanks to which you will no longer have to worry about blackouts because if the power grid goes out, this panel can automatically start the generator and allow you to continue your activity without losing your work data.

### **VISA P14SG TECHNICAL CHARACTERISTICS**

Phase Type: Single Phase / Three Phase  
Maximum power: 14 KVA / 11 KW  
Continuous power: 13 KVA / 10 KW  
Fuel: Diesel  
Voltage: 230 / 400 V  
Frequency: 50 Hz  
Engine: Perkins 403A-15G1  
Emission standard: Not Emitted  
Number of cylinders: 3  
Engine speed: 1500 rpm  
Starter: Electric  
Control unit: Comap AMF 25  
Voltage regulator: AVR  
Socket panel: Terminal block (Power socket)  
Tank capacity: 50 Lt  
Consumption: 2.8 Lt/h at 75% load  
Autonomy: 17.85 h at 75% load  
Acoustic pressure: 60 dB(A) @ 7m  
Length: 1802 mm  
Width: 752 mm  
Height: 1130 mm  
Net weight: 571 kg

Are you looking for a generator set with different technical characteristics? [HERE](#) you can find the area dedicated to VISA generator sets or other specialized brands.

The images are purely indicative.

---



**Product features:**

Phase: Single phase / Three phase  
Maximum power three phase (KW): 11  
Continuous power three phase (KW): 10  
Maximum power three phase (KVA): 14  
Continuous power three phase (KVA): 13  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: Terminal box  
Engine: Perkins 403A-15G1  
Emissions Regulations: Not Emitted  
Engine rpm (rpm): 1500  
Starting system: Electric  
Number cylinders: 3  
Cooling: Water  
Alternator: STAMFORD S0L1-H  
Fuel tank capacity (L): 50  
Consumption (L/h): 2.8 at 75% of the load  
Running time (h): 17.5 at 75% of the load  
Acoustic pressure: 60 dB(A) at 7 m  
Length (mm): 1802  
Width (mm): 752  
Height (mm): 1130  
Dry weight (Kg): 571  
ATS Switch device : Optional  
Voltage regulator: AVR  
Engine manufacturer: Perkins

