



# WEBASTO BLUECOOL C-40T NAUTICAL CHILLER AIR CONDITIONER 40000 BTU/h

## Product description:

### **WEBASTO BLUECOOL C-40T NAUTICAL CHILLER AIR CONDITIONER 40000 BTU/h**

Webasto BlueCool C-40T is a chilled water nautical air conditioner (chiller) suitable for use on boats, with a rated cooling capacity of 40000 BTU/h.

The Webasto BlueCool C-40T is a nautical air conditioner designed to provide an effective and reliable solution for air conditioning the indoor environment of boats. Thanks to its cooling capacity, the air conditioner ensures optimal comfort in all weather conditions.

The Webasto BlueCool C-40T is a water chiller that uses a refrigeration circuit to cool water and then distributes it through a system of pipes and fans. This method of cooling offers many advantages, including quiet operation and even distribution of cool air inside the boat.

The system is designed for easy and convenient installation aboard boats. Its compact size and sleek design allow it to blend harmoniously into its surroundings. In addition, the system features an intuitive display for easy and precise control of temperature settings and other functions.

The Webasto BlueCool C-40T chiller air conditioner can provide cooling to different areas of the boat, allowing the temperature in each room to be adjusted separately. This provides precise control of thermal comfort and the ability to meet the individual preferences of each passenger on board.

The advanced technology of the Webasto BlueCool C-40T ensures quiet operation, allowing you to enjoy a cool and comfortable environment without annoying noise. In addition, the system is designed to be highly energy efficient, helping to reduce fuel consumption and operating costs.

The WEBASTO BLUECOOL C-40T comes complete with:



electronics

blower

Touch Screen remote panel with 4.5 m cable

### **TECHNICAL FEATURES WEBASTO BLUECOOL C-40T**

Cooling capacity: 40000 BTU/h / 11700W

Heating Capacity: 40000 BTU/h / 11700W

Power Supply Voltage: 230V

Frequency: 50 / 60 Hz

Operating current consumption: 14 / 16 A

Minimum cold water flow rate: 32 l/min

Ø cold water connection: 1"

Ø seawater connection: 1"

Minimum seawater flow rate: 34 l/min

Max. permissible ambient temperature: 45 °C

Refrigerant: R410a

Refrigerant quantity: 2x650 g

Width: 590 mm

Depth: 410 mm

Height: 500 mm

Net weight: 70 kg

Looking for a product with different technical characteristics? [Here](#) you can find the area dedicated to nautical air conditioners WEBASTO or other specialized brands.

Images and technical data are not binding.

### **Product features:**

Phase: Single phase

Frequency (Hz): 50

Voltage (V): 230

Refrigerating yield: 40000 BTU/h / 11700 W

Heating power: 40000 BTU/h / 11700W

Absorbed average current, refrigerating (A): 14 / 16

Length (mm): 590

Width (mm): 410

Height (mm): 500

Product type: Air conditioner

Coolant: R410A

Weight (Kg): 70

---