



GENERATOR SINGLE- PHASE / THREE-PHASE 200KVA WITH MANUAL CONTROL PANEL STAGE V

Product price:

48,652.00 € tax excluded

Product description:

GENERATOR SINGLE-PHASE / THREE-PHASE 200KVA with manual control panel

Single/three phase 200KVA generator with a 1500 rpm Perkins diesel engine, compact and easy to use, mounted on a fixed base. The is equipped with a weatherproof, structural steel sheet soundproof cabin and an interior cladding of high noise reduction material, making the supersilenced.

The generator consists of a self-excited, brushless alternator with AVR voltage regulator. The generator is equipped with an electric starter with a low fuel consumption battery, consuming only 31,4 litres per hour at 75% load. The fuel tank is incorporated in the crankcase for ease of use.

This generator is perfect for use outdoors, such as on construction sites.

The generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

Technical characteristics of the generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 176 KW / 220 KVA

Three-phase continuous power: 160 KW / 200 KVA

Maximum single-phase power: 58.67 KW / 73.33 KVA

Single-phase continuous use power: 53.33 KW / 66.67 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: FPT NEF N67 TEVP05.00

Engine speed: 1500 rpm

Starting: Electric

Consumption: 31.4 Lt/h at 75% load

Length: 3600 mm

Width: 1200 mm

Height: 2300 mm

Weight: 3200 Kg

Super-silenced

AVR



If you are looking for a product like the then you can browse the full range of [generators](#) or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 58.67
Continuous power single phase (KW): 53.33
Maximum power single phase (KVA): 73.3
Continuous power single phase (KVA): 66.67
Maximum power three phase (KW): 176
Continuous power three phase (KW): 160
Maximum power three phase (KVA): 220
Continuous power three phase (KVA): 200
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: Terminal box
Engine: FPT NEF N67 TEVP05.00
Emissions Regulations: Stage 5
Engine rpm (rpm): 1500
Speed governor: Electronic
Starting system: Electric
Engine capacity (cm³): 6
Number cylinders: 6
Cooling: Water
Alternator: Brushless
Poles: 4
Protection degree: IP44
Bore x stroke (mm): 104 x 132
Fuel tank capacity (L): 250
Consumption (L/h): 31.4 at 75% of the load
Running time (h): 8 at 75% of the load
Acoustic pressure: 69 dB(A) at 7 m
Length (mm): 3600
Width (mm): 1200
Height (mm): 2300
Dry weight (Kg): 3200
AVR: Yes
Silenced: Yes
Super silenced: Yes



Shop name

Product type: Generator

ATS Switch device : No

Voltage regulator: AVR

Engine manufacturer: FPT Iveco



PrestaShop