



# PRAMAC GPW60 I/FS5 GENERATOR 60KVA SING LE-PHASE/THREE-PHASE STAGEV AUTOMATIC PANEL

**Product price:**

**28,153.62 € tax excluded**

## **Product description:**

### **PRAMAC GPW60 I/FS5 GENERATOR 60KVA SINGLE-PHASE/THREE-PHASE STAGEV AUTOMATIC PANEL**

The PRAMAC GPW60 I/FS5 single-phase/three-phase generator is equipped with an Iveco FPT F34TEVP01 StageV diesel engine and is capable of delivering a maximum power of 60 KVA, complete with an **Automatic Voltage Regulator (AVR)**.

The PRAMAC GPW60 I/FS5 generator comes with electric, manual, or automatic starting options using a 12V battery. It features a **Deep Sea 7320 controller** that displays all electrical parameters of the engine and generator, operational functions, generator status, and allows comprehensive management of the generator. It also displays any potential system errors or alarms.

Thanks to the included AVR, the PRAMAC GPW60 I/FS5 generator can deliver "clean" current and voltage with precision of less than one percent. This ensures safe connection of any electrical and electronic devices.

The PRAMAC GPW60 I/FS5 generator ensures efficient and quiet operation, powered by the Iveco FPT F34TEVP01 StageV engine, capable of delivering a maximum power of 60 KVA.

## **PREPARATION FOR AUTOMATIC START PANEL (ATS)**

The generator is prepared for use with an Automatic Start Panel (ATS), which automatically starts the generator in case of a power outage. This feature ensures uninterrupted operation and data retention during power interruptions.



## STAGEV EMISSIONS REGULATION

The generator is equipped with a StageV "mobile" engine, as required by European Regulation 2016/1628. These new engines significantly reduce particulate and nitrogen oxide emissions into the environment, reducing environmental impact by 200% compared to standard engines.

### Standard Equipment:

Starting batteries  
Battery disconnect switch  
Plastic 80L fuel tank  
Spillage collection basin  
Galvanized base skid  
Socket Kit: 1 x 400V CEE 63A 3P+N+T IP67 | 1 x 400V CEE 32A 3P+N+T IP67 | 1 x 400V CEE 16A 3P+N+T IP67 | 1 x 230V CEE 16A 2P+T IP67 | 1 x 230V 16A Schuko IP68  
MECC ALTE alternator with AVR

## TECHNICAL SPECIFICATIONS PRAMAC GPW60 I/FS5

Phase Type: Single-Phase / Three-Phase  
Continuous Use Power: 60.3 KVA / 48.2 KW  
Maximum Power: 60.3 KVA / 48.2 KW  
Engine: Iveco FPT F34TEVP01  
Emissions Regulation: Stage V  
Engine Speed: 1500 rpm  
Starting: Electric / Automatic  
Fuel: Diesel  
Voltage at Terminals: 230 / 400 V  
Frequency: 50 Hz  
Voltage Regulator: AVR  
Socket Panel: 1 x 400V CEE 63A | 1 x 400V CEE 32A | 1 x 400V CEE 16A | 1 x 230V CEE 16A | 1 x 230V 16A Schuko  
Tank Capacity: 80 l  
Consumption at 75% Load: 10.9 l/h  
Autonomy at 75% Load: 7.3 h  
Sound Pressure: 64 dB(A) @ 7 m  
Length: 2400 mm  
Width: 1040 mm  
Height: 1745 mm  
Dry Weight: 1250 Kg

Looking for a generator with different technical specifications? Check out the [dedicated section](#) for PRAMAC generators or other specialized brands.

Images and technical data are not binding.

**Product features:**

Phase: Single phase / Three phase

Maximum power three phase (KW): 48.2

Continuous power three phase (KW): 48.2

Maximum power three phase (KVA): 60.3

Continuous power three phase (KVA): 60.3

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Engine: Iveco FPT F34TEVP01

Emissions Regulations: Stage 5

Engine rpm (rpm): 1500

Speed governor: Electronic

Starting system: Electric / Automatic

Engine capacity (cm<sup>3</sup>): 3400

Number cylinders: 4

Cylinders' position: In line

Cooling: Water

Alternator: Mecc alte ECP32-2M4

Poles: 4

Fuel tank capacity (L): 80

Consumption (L/h): 10.9 at 75% load

Running time (h): 7.3 at 75% load

Acoustic pressure: 64 dB(A) at 7 m

Length (mm): 2400

Width (mm): 1040

Height (mm): 1745

Dry weight (Kg): 1250

Silenced: Yes

Super silenced: Yes

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: FPT Iveco

Video: cqL-3OfWU1Q

