



VICTRON MultiPlus C 12/2000/80-30 Charger- Inverter 12V 30A

Product price:

1.055,00 € tax excluded

Product description:

VICTRON MultiPlus C 12/2000/80-30 Charger-Inverter 12V 30A

VICTRON MultiPlus C 12/2000/80-30 powerful pure sine wave inverter and charger adaptive charging technology and a high-speed AC transfer switch.

The VICTRON MultiPlus C 12/2000/80-30 is an advanced 12V 30A charger-inverter, carefully designed to meet the challenges of advanced energy management. This device boasts a wide range of features that solidify its role as a crucial component within energy systems.

The Multi Control panel allows a maximum current to be set for the generator or ground connection, preventing overloads from external sources. The innovative integration of PowerControl enables the VICTRON MultiPlus C 12/2000/80-30 to seamlessly integrate alternative energy sources.

By enhancing battery charging through a sophisticated four-stage adaptive charger, the VICTRON MultiPlus C 12/2000/80-30 employs adaptive charging software to adapt to prevailing conditions. This progressive process moves smoothly through three automatic stages, with a fourth stage dealing with extended operating periods.

To ensure safety, the VICTRON MultiPlus C 12/2000/80-30 is equipped with a programmable relay. This relay can be configured to act as an alarm, facilitating disconnection during pre-alarm or alarm scenarios, thus providing an additional level of safety.

For convenient remote management, a three-pin connector simplifies operations, enabling remote activation, deactivation, and control of the charger. After installation, the VICTRON MultiPlus C 12/2000/80-30 is ready for use, while the option to adjust settings via DIP switches adapts to the specific needs of each power system.

TECHNICAL CHARACTERISTICS VICTRON MultiPlus C 12/2000/80-30



PowerControl: Yes
Parallel and three-phase operation: Yes
Transfer switch: 30 A

INVERTER

Input voltage range: 9.5 to 17 V
Output voltage: 230 VAC \pm 2%
Frequency: 50 Hz \pm 0.1%
Continuous output power at 25?: 2000 VA
Continuous output power at 25? / 40? / 65?: 1600 W / 1400 W / 1000 W
Peak power 4000 W
Maximum efficiency 93 %
Zero load power supply in AES mode: 7 W
Zero load power supply in Search mode: 3 W

CHARGER

Input voltage range: 187-265 VAC
Input frequency: 45-65Hz
Charging voltage "absorption": 14.4 V
"Hold" charging voltage: 13.8 V
Storage mode: 13.2 V
Service battery charging current: 80A
Battery charging current: 4A
Battery temperature sensor: Yes

Width: 255 mm
Length: 125 mm
Height: 520 mm
Weight: 12kg

Looking for a product with different technical specifications? Here you can find the complete range of VICTRON chargers and inverters, as well as other specialized brands.

Images and technical data are not binding.

Product features:

Phase: Single phase
Frequency (Hz): 50
Voltage (V): 187-265
Protection degree: IP21
Output voltage (V): 230
Nominal current (A): 14.4



Charging voltage (V): 12

Length (mm): 255

Width (mm): 125

Height (mm): 520

Overload protectors: Yes

Input voltage (V): 12

Kind of wave: Pure Sinusoidal

Continuous power (W): 1600

Colour: Blue

Weight (Kg): 15.5