



GENERATING SET 45KVA WITH AUTOMATIC CONTROL PANEL

Product price:

11,663.00 € tax excluded

Product description:

Single/three-phase 45KVA generator super-silenced with automatic control pane

Technical characteristics of the generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 40 KW / 50 KVA
Three-phase continuous power: 36 KW / 45 KVA
Maximum single-phase power: 13.33 KW / 16.67 KVA
Single-phase continuous use power: 12 KW / 15 KVA

Fuel: Diesel

Voltage: 230 V / 400 V Frequency: 50 Hz

Motor: FPT NEF N45AM1A Engine speed: 1500 rpm

Starting: Electric

Consumption: 8.8 Lt/h at 75% load

Length: 2000 mm Width: 850 mm Height: 1275 mm Weight: 930 Kg Super-silenced

AVR

Images and technical data are not binding.



Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 13.3 Continuous power single phase (KW): 12 Maximum power single phase (KVA): 16 Continuous power single phase (KVA): 15 Maximum power three phase (KW): 40 Continuous power three phase (KW): 36 Maximum power three phase (KVA): 50 Continuous power three phase (KVA): 45

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 230 / 400

Sockets configuration: Terminal box

Engine: FPT NEF N45AM1A Emissions Regulations: Stage 2

Engine rpm (rpm): 1500 Speed governor: Mechanical Starting system: Electric Engine capacity (cm³): 4500

Number cylinders: 4 Cooling: Water

Alternator: Brushless

Poles: 4

Protection degree: IP44

Bore x stroke (mm): 104 x 132 Fuel tank capacity (L): 100 Consumption (L/h): 8.8 Running time (h): 11.4

Acoustic pressure: 69 dB(A) at 7 m

Length (mm): 2000 Width (mm): 850 Height (mm): 1275 Dry weight (Kg): 930

AVR: Yes Silenced: Yes

Super silenced: Yes Product type: Generator ATS Switch device: Optional

Voltage regulator: AVR

Engine manufacturer: FPT Iveco

