



HYUNDAI H3750iE GASOLINE GENERATOR SINGLE PHASE STAGE V INVERTER 3 KW

Product price:

856,47 € tax excluded

Product description:

HYUNDAI H3750iE GASOLINE GENERATOR SINGLE PHASE STAGE V INVERTER 3 KW

The HYUNDAI H3750iE single phase generator, is equipped with a 4-stroke **StageV** engine supplied by gasoline, delivers a maximum power of 3KW, complete with inverter voltage regulator.

HYUNDAI H3750iE is equipped with electric start with battery.

The HYUNDAI H3750iE generator provides reliable power for home, work and leisure environments, safely appliances and other electronic devices. Extremely convenient sockets and controls make it easy to start and operate the generator, making these tasks extremely quick and easy.

The HYUNDAI H3750iE generator has a convenient double-curved handle for easy mobility and storage. HYUNDAI H3750iE has a robust structure and a tank with a maximum capacity of 12 lt.

EMISSION STANDARD STAGEV

HYUNDAI H3750iE is equipped with "mobile" STAGEV motorization, as required by European Regulation 2016/1628. These new engines make it possible to exponentially reduce the particulate and nitrogen oxide emissions delivered by the generator into the environment, and ensure a 200% reduction in environmental impact compared to standard engines.

TECHNICAL CHARACTERISTICS HYUNDAI LS 65003

Phase type: Single-phase

Continuous use power: 3 KVA / 3 KW



Maximum power 3.3 KVA / 3.3 KW

Engine: 4-stroke

Engine revolutions: 3000 rpm

Emissions standard: StageV

Starting: Electric

Fuel: Gasoline

Voltage: 230 V

Frequency: 50Hz

Socket panel: 2 x CEE 16A 230V

Tank capacity: 12 l

Sound pressure: 64 dB (A) @ 7 m

Length: 645 mm

Width: 490 mm

Height: 585 mm

Dry weight: 45 Kg

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the area dedicated to HYUNDAI generators or other specialized brands.

Images and technical data are not binding.

Product features:

Phase: Single phase

Maximum power single phase (KW): 3.3

Continuous power single phase (KW): 3

Maximum power single phase (KVA): 3.3

Continuous power single phase (KVA): 3

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230

Sockets configuration: 2 x CEE 16A 230V

Emissions Regulations: Stage 5

Engine rpm (rpm): 3000

Starting system: Electric

Alternator: Avvolgimento in rame

Fuel tank capacity (L): 12

Running time (h): 6

Acoustic pressure: 64 dB(A) at 7 m

Length (mm): 645

Width (mm): 490

Height (mm): 585

Dry weight (Kg): 91



Silenced: Yes

Super silenced: Yes

ATS Switch device : No

Voltage regulator: Inverter