



# VISA F120GX GENERATOR SET SILENCED 124 KVA AVR

# **Product price:**

16,520.00 € tax excluded

### **Product description:**

### **GENERATING UNIT VISA F120GX**

The VISA F120GX silenced land-based generator set, rated at 124 KVA in continuous use and AVR, mounts top brand components: the VISA F120GX model uses a reliable FPT IVECO N45TM3 4-cylinder, 1500-rpm diesel engine and a **STAMFORD UCI274E** alternator equipped with AVR with 1% voltage regulation accuracy.

The VISA industrial power generators feature silenced casings and tropicalized treatment, thus they are suitable for use in hot climates; in particular the VISA F120GX is water-cooled, which guarantees excellent heat management.

The robust frame of the silenced VISA F120GX genset contains a capacious 160-litre tank, guaranteeing a 7-hour autonomy at 75% load; furthermore, the dimensions of this generator are optimised for its transport by truck and its storage in a 40' HC container.

## Technical characteristics of the VISA F120GX generator set:

Phase type: Three-phase

Maximum three-phase power: 135 KVA Maximum three-phase power: 108 KW Three-phase continuous power: 124 KVA Three-phase continuous power: 99.2 KW

Fuel: Diesel Voltage: 400 V Frequency: 50 Hz

Engine: FPT IVECO N45TM3 Engine speed: 1500 rpm

Starter: Electric

Consumption: 20.4 Lt/h at 75% load

Length: 2560 mm



Width: 1040 mm Height: 1805 mm Weight: 1690 Kg Supersilenced

**AVR** 

If you are looking for a product such as the VISA F120GX then you can browse the entire VISA generator range or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

#### **Product features:**

Phase: Three phase

Maximum power three phase (KW): 108 Continuous power three phase (KW): 99.2 Maximum power three phase (KVA): 135 Continuous power three phase (KVA): 124

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 400

Sockets configuration: Terminal box

Engine: FPT (IVECO) N45TM3, 4 stroke turbo-aftercooler

Emissions Regulations: Stationary Use

Engine rpm (rpm): 1500 Starting system: Electric Engine capacity (cm³): 4500

Number cylinders: 4

Cooling: Water Poles: 4

Fuel tank capacity (L): 160 Consumption (L/h): 20.4 Running time (h): 7.8 Length (mm): 2560

Width (mm): 1040 Height (mm): 1805 Dry weight (Kg): 1690

Silenced: Yes

Product type: Generator Voltage regulator: AVR

Engine manufacturer: FPT Iveco

Video: i6KAsizOxDQ



