



VISA P105GX GENERATOR SET SILENCED 100 KVA AVR

Product price:

18,408.00 € tax excluded

Product description:

GENERATING UNIT VISA P105GX

The VISA P105GX silenced land-based generator set, rated at 100 KVA in continuous use and AVR, mounts top brand components: the VISA P105GX model uses a reliable PERKINS 1104C-44TAG2 4-cylinder, 1500-rpm diesel engine and a **STAMFORD UCI274C** alternator equipped with AVR with 1% voltage regulation accuracy.

The VISA industrial power generators feature silenced casings and tropicalized treatment, thus they are suitable for use in hot climates; in particular the VISA P105GX is water-cooled, which guarantees excellent heat management.

The robust frame of the silenced VISA P105GX genset contains a capacious 160-litre tank, guaranteeing a 9-hour autonomy at 75% load; furthermore, the dimensions of this generator are optimised for its transport by truck and its storage in a 40' HC container.

Technical characteristics of the VISA P105GX generator set:

Phase type: Three-phase

Maximum three-phase power: 110 KVA

Three-phase continuous power: 88 KW

Maximum three-phase power: 100 KVA

Three-phase continuous power: 80 KW

Fuel: Diesel

Voltage: 400 V

Frequency: 50 Hz

Engine: PERKINS 1104C-44TAG2

Engine speed: 1500 rpm

Starter: Electric

Consumption: 17.1 Lt/h at 75% load

Length: 2560 mm



Width: 1040 mm

Height: 1805 mm

Weight: 1650 Kg

Supersilenced

AVR

If you are looking for a product such as the VISA P105GX then you can browse the entire VISA [generator](#) range or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Product features:

Phase: Three phase

Maximum power three phase (KW): 88

Continuous power three phase (KW): 80

Maximum power three phase (KVA): 110

Continuous power three phase (KVA): 100

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Sockets configuration: Morsettiera

Engine:

Emissions Regulations: Stationary Use

Engine rpm (rpm): 1500

Starting system: Elettrico

Engine capacity (cm³): 4400

Number cylinders: 4

Cooling: Water

Poles: 4

Fuel tank capacity (L): 160

Consumption (L/h):

Running time (h): 9.3

Length (mm):

Width (mm): 1040

Height (mm): 1805

Dry weight (Kg): 1650

Silenced: Yes

Product type: Generator

Voltage regulator: AVR

Engine manufacturer: Perkins