



MOSA GE 65 FSX 60Hz GENERATOR 66 KVA SINGLE-PHASE / THREE- PHASE AVR

Product price:

14,868.00 € tax excluded

Product description:

MOSA GE 65 FSX 60Hz GENERATOR 66 KVA SINGLE-PHASE / THREE-PHASE AVR

The MOSA GE 65 FSX 60Hz single/three-phase generator is equipped with a diesel-powered FPT N45SM1A engine, and is capable of delivering a maximum power of 66 KVA with automatic voltage regulator AVR.

The MOSA GE 65 FSX is equipped with **electric, manual or automatic start** with 12 V battery, and is equipped with **COMAP AMF 9 NT control unit** which allows to view all the electrical parameters of the engine, the functions, the status of the generator, manage the entire group and view, in case they occur, the errors or alarms of the system.

The COMAP AMF 9 NT control unit is one of the most complete versions of controllers for generating. The possibility of expanding the number of digital inputs and outputs makes it very flexible, suitable for generating with numerous connected elements. The expansion module allows you to add internet, SMS and MODBUS connectivity to the remote control of the machine. The easy-to-use backlit display allows you to view every parameter of the generating.

Thanks to the AVR voltage regulator included in the supply of the group, the MOSA GE 65 FSX is able to supply "clean" current and voltage with an accuracy of less than one percent, this guarantees the user to be able to safely connect any type of electrical and electronic device.

The MOSA GE 65 FSX guarantees efficient and silent operation thanks to the FPT N45SM1A engine, which to deliver a maximum power of 66KVA.

AVR VOLTAGE REGULATOR



The MOSA GE 65 FSX is supplied complete with AVR. The AVR is a device that allows you to **keep the output more constant and less dependent on the load**. Thanks to the AVR there are fewer current drops or peaks and this makes the use of the various connected devices safer, improving their performance and duration.

ATS AUTOMATIC START-UP PANEL (OPTIONAL)

The MOSA GE 65 FSX is set up for the use of an ATS automatic starting panel. Thanks to which you will no longer have to worry about blackouts because if it goes off the electricity grid this panel is able to automatically start the generator and will allow you to continue your business without losing your work data.

TECHNICAL FEATURES MOSA GE 65FSX

Phase type: Single / Three phase

Singlephase maximum output: 22 KVA / 17.6 KW

Singlephase continuous output: 20 KVA / 16 KW

Threephase maximum output: 66KVA / 52.8 KW

Threephase continuous output: 60KVA / 48 KW

Fuel: Diesel

Voltage: 120 / 220 V

Frequency: 60 Hz

Motor: FPT N45SM1A

Regulations emissions: Stage 0

Number of cylinders: 4

Engine revolutions: 1500 rpm

Starting: Electric

Voltage regulator: AVR HVR-30

Tank capacity: 100 Lt

Consumption: 12.3 Lt / h at 75% of the load

Autonomy: 8 h at 75% of the load

Acoustic pressure: 66 dB (A) @ 7m

Length: 2165 mm

Width: 900 mm

Height: 1403 mm

Weight: 1210 Kg

Are you looking for a product with different technical characteristics? [HERE](#) you can find the area dedicated to MOSA generators or other specialized brands.

The images are purely indicative.

**Product features:**

Phase: Single phase / Three phase

Maximum power single phase (KW): 17.6

Continuous power single phase (KW): 16

Maximum power single phase (KVA): 22

Continuous power single phase (KVA): 20

Maximum power three phase (KW): 52.8

Continuous power three phase (KW): 48

Maximum power three phase (KVA): 66

Continuous power three phase (KVA): 60

Fuel: Diesel

Frequency (Hz): 60

Voltage (V): 120 / 220

Sockets configuration: Terminal box

Engine: FPT N45SM1A

Emissions Regulations: Stationary Use

Engine rpm (rpm): 1500

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 4500

Number cylinders: 4

Cooling: Water

Inyección : Direct

Alternator: Sincrono trifase, autoeccitato, autoregolato, senza spazzole

Fuel tank capacity (L): 100

Consumption (L/h): 12.3 @75% del carico

Running time (h): 8 at 75% of the load

Acoustic power: 92 dB(A)

Acoustic pressure: 67 dB(A) at 7 m

Length (mm): 2165

Width (mm): 900

Height (mm): 1403

Dry weight (Kg): 1200

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: FPT Iveco

