



# Vitrifrigo Centrifugal Seawater Pump

**Product price:**

**624,51 € tax excluded**

## Product description:

### VITRIFRIGO CENTRIFUGAL SEAWATER PUMP

The VITRIFRIGO Centrifugal Seawater Pump with open impeller represents an excellent solution for water distribution needs aboard yachts and boats. This pump is part of the renowned MACS - Chiller Units and Accessories line, offering reliable and durable performance to ensure a constant and uniform flow.

With a power supply of 230V/1ph/50Hz and a current draw of 2.8A, this VITRIFRIGO pump is designed for energy efficiency and long-term use without issues of overheating or overload. The inlet and outlet, both with a diameter of 1 mm, allow for smooth and even distribution with an impressive flow rate. With a flow rate ranging from 1500 to 4800 liters per hour at various lift heights, this VITRIFRIGO pump can adapt to a wide range of distribution needs.

The compact dimensions of the VITRIFRIGO with open impeller, measuring 303 mm in length, 177 mm in width, and 161 mm in height, make it suitable even for limited spaces aboard. Despite weighing 9.1 kg, this VITRIFRIGO pump is characterized by a robust construction that ensures reliable water distribution at all times.

Furthermore, thanks to its open impeller, the VITRIFRIGO Centrifugal Seawater Pump offers quiet and vibration-free operation, helping to maintain a comfortable and peaceful environment during navigation. With its advanced technology and open impeller design, the VITRIFRIGO Centrifugal Seawater Pump guarantees high performance and uniform distribution, enhancing the sailing experience and the crew's comfort aboard vessels.

## Technical specifications VITRIFRIGO Seawater Pump Centrifuge:





Power supply: 230V/1ph/50Hz  
Absorbed current: 2.8 A  
Water inlet: 1 mm.  
Water outlet: 1 mm.  
Flow rate: 1500/12,2 m - 3000/11,5 m - 4800/9 m lt/h  
Length: 303 mm.  
Width: 177 mm.  
Height: 161 mm.  
Weight: 9.1 Kg

Are you looking for a marine air conditioner? [HERE](#) you can find the area dedicated to Vitrifrigo marine air conditioners or other specialized brands.

Non-binding images and technical data.

**Product features:**

Maximum permissible current (A): 2.8  
Length (mm): 303  
Width (mm): 177  
Height (mm): 161  
Dry weight (Kg): 9.1  
Feed Type: 230V/1ph/50Hz  
Capacity (Lt/h): 1500/12,2 m - 3000/11,5 m - 4800/9 m lt/h  
Water Inlet (mm.): 1  
Water Outlet: 1