

# RIELLO UPS SEP3000ER 3000VA



## Product description:

### CHARACTERISTICS

Filtered, stabilised and reliable voltage: ON LINE double conversion technology (VFI according to IEC 62040-3) with filters for atmospheric noise suppression;  
High overload capacity (up to 150%);  
Programmable auto restart at mains return;  
Battery ignition (Cold Start);  
Load power factor correction (UPS input power factor close to 1);  
Wide input voltage tolerance range (from 140 V to 276 V) without battery intervention;  
Expandable autonomy for several hours;  
Fully configurable via UPS Tools configuration software;  
High battery reliability (automatic and manually activated battery test);  
High UPS reliability (total microprocessor control);  
Low impact on mains (sinusoidal absorption).

### ADVANCED COMMUNICATION

Multiplatform communication for all operating systems and network environments: PowerShield3 monitoring and shutdown software for Windows 10, 8, 7, Hyper-V, 2019, 2016, 2012 and earlier versions, Mac OS X, Linux, VMWare ESXi, Citrix XenServer and other Unix operating systems;  
UPS Tools configuration and customisation software supplied as standard;  
RS232 serial port and opto-isolated contacts;  
USB port;  
Slot for communication cards.

Images and technical data are not binding.



---

**Product features:**

Phase: Single phase

Frequency (Hz): 50 / 60

Voltage (V): 220 / 230 / 240

Power (VA): 3000

Battery type: VRLA/AGM/GEL/NiCd/Liion/Supercaps

Operating temperature (°C): 0 °C / +40 °C

Length (mm): 446

Width (mm): 190

Height (mm): 333

Dry weight (Kg): 15

Colour: Black