



Used GE Generator Set 800KVA PERKINS Single-Phase - Three-Phase

Product price:

86,710.00 € tax excluded

Product description:

USED GE GENERATOR SET 800KVA PERKINS SINGLE-PHASE - THREE-PHASE

Generator Set GE 800KVA PERKINS single-phase / three-phase equipped with PERKINS 3012TAG3A Diesel

engine capable of delivering a maximum power of 800KVA, complete with voltage regulator.

Generator Set GE 800KVA PERKINS is compact and easy to use, equipped with soundproofed casing

with panels that significantly reduce acoustic emissions, making it super-silent.

The 800KVA generator set consists of a MARELLI alternator and voltage regulator. The GE 800KVA generator

set is equipped with electric start and has low fuel consumption,

consuming only 127 liters per hour at 75% load for up to 7.87 hours of operation.

The GE 800KVA generator set is equipped with electric start or automatic start via ATS panel, allowing automatic start in case of blackout.

AUTOMATIC START ATS PANEL

The GE 800KVA generator set is designed for use with an automatic start ATS panel. Thanks to this,

you no longer have to worry about blackouts because if the power grid goes out, this panel will automatically start the GE 800KVA, allowing you to continue your activities without losing your work data.

Technical Specifications of GE 800KVA:

Phase Type: Single-phase / Three-phase

Maximum Single-phase Power: 266 KVA / 213KW



Maximum Three-phase Power: 800 KVA / 640KW

Power Factor cos fi?: 0.8 Voltage VAC: 230 / 400 V

Frequency (Hz): 50 Voltage Regulator: Yes

Starting Panel: Manual / Automatic Engine: PERKINS 3012TAG3A Revolutions per minute RPM: 1500

Fuel: Diesel

Tank Capacity: 1000 I

Consumption @ 75% load: 127 l/h Autonomy @ 75% load: 7.87 h Sound Pressure: 75 dB(A) @ 7m Emission Regulation: Stationary Use

Length: 5500 mm Width: 2100 mm Height: 2500 mm Net Weight: 8200 Kg

Are you looking for a used genset with different technical characteristics? View a similar product by clicking <u>HERE</u>.

Le immagini sono puramente indicative.

Product features:

Phase: Single phase / Three phase Maximum power single phase (KW): 21 Maximum power single phase (KVA): 266 Maximum power three phase (KW): 640 Maximum power three phase (KVA): 800

Fuel: Diesel

Frequency (Hz): 50 / 60 Voltage (V): 230 / 400

Sockets configuration: Terminal box Engine: PERKINS 3012TAG3A

Emissions Regulations: Stationary Use

Engine rpm (rpm): 1500 Speed governor: Mechanical

Starting system: Manual / Automatic

Cooling: Air



Alternator: Marelli

Poles: 4

Fuel tank capacity (L): 100

Consumption (L/h): 127 Lt/h at 75% load Running time (h): 7.87 h at 75% load

Length (mm): 5500 Width (mm): 2100 Height (mm): 2500 Dry weight (Kg): 8200

Silenced: Yes

Super silenced: Yes

ATS Switch device : Optional

Voltage regulator: YES

Engine manufacturer: Perkins

